






REV.	ECN NO	OR DESCRIPTION	REVISED	DATE
A	PDR NO.:T120215-BA	ULY		2012.07.25
B	ECN NO.S141055	JF		2015.01.23



PACKAGING



- NOTES:
1. WATERPROOF RATE: IP67
 2. CURRENT RATING: 2A
 3. ELECTRICAL CHARACTERISTICS:
 - 3-1. CONTACT RESISTANCE : 10 mΩ MAX.
 - 3-2. HI-POT TEST 500VAC 5mA(1min)
 - 3-3. INSULATION RESISTANCE: 100Mohm MIN. BY 500V DC
 4. TEMPERATURE RATING : -20℃ ~ +80℃
 5. SPECIFICATIONS:SEE "D-SUB SERIES SPECIFICATIONS".
 6. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
 7. GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING:
 8. FOR CABLE OD:φ4.0mm~φ7.0mm

L	GASKET	1	EPDM	BLACK
K	MALE PIN	15	Brass(HB59-1.5B)	(1~3)u" GOLD PLATING OVER NICKEL PLATING
J	INSULATOR	2	PBT	BLACK
I	SHELL	2	COLD ROLLER STEEL	NICKEL PLATING 60u"
H	HOUSING	1	ABS 765A UL94V-0	BLACK
G	O-RING 3	2	SILICONE	CLEAR
F	O-RING 2	2	EPDM	BLACK
E	GASKET	1	SILICONE	BLACK
D	SCREW	2	HB59-1.5B	NICKEL PLATING 100u"
C	CLAMP RING	1	PPE 540Z	BLACK
B	SEAL	1	EPDM	BLACK
A	SEALING NUT	1	PPE 540Z	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
DECIMALS: ANGLES:				
X	:±0.5	X	:±2°	
XX	:±0.3	XX	:±1°	
XXX	:±0.2			
TITLE D-SUB (IP67) MALE CONN. MALE 15 PIN SCREW TYPE				
DMN	JF	PART NO.	2DS3001-W15200H	
CHKD	Horlen	SCALE	1:1	UNIT: mm
APVD	Steve	SIZE: A3	SHEET: 1 OF 1	REV: B

CUSTOMER COPY