





REV	ECN NO. OR DESCRIPTION	REVISED	DATE
A	PDR NO.:T250508-6B	Jun	2026.04.10



A VIEW

3	GREEN
2	BLUE
1	YELLOW
CONN.	COLOR
PIN DEFINE	
CONN.	



Pin Assignments
Front View

- NOTES:
1. WATERPROOF GRADE: IPX5
 2. CURRENT RATING: 15A
 3. HI-POT TEST 800V AC, 5mA(1SEC)
 4. INSULATION RESISTANCE: 30MΩ Min. BY 500V DC
 5. SPECIFICATIONS:SEE "E-BIKE SERIES SPECIFICATIONS".
 6. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
 7. GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING:
 8. LASER PRINT DATE CODE: YYMMDD



E	CABLE	1	16AWG*3C OD5.6	BLACK(PVC JACKET)
D	OVER MOLD	1	TPU	BLACK
C	INNER MOLD	1	PVC	BLACK
B	MALE PIN	1	BRASS	1~3μ" GOLD PLATING OVER NICKEL PLATING
A	BODY	1	PA66+GF	BLACK
NO.	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
DECIMALS: ANGLES:				
X	±0.5	X	±1°	
X.X	±0.3	X.X	±0.5°	
X.XX	±0.2			
TITLE E-BIKE SERIES 180° 3 PIN MALE CONN.				
DWN	Jun	PART NO.	2EB3024-W034A1H	
CHKD	Allen	SCALE 2:1	UNIT: mm	
APVD	Liao	SIZE: A3	SHEET:1 OF 1	REV: A
CUSTOMER COPY				