



REV	LOCAS	DESCRIPTION	DRAW	DATE
01	NEW	INITIAL RELEASE	Junly	2010.08.16
05	△05	ECN20120040	Huang	2012.09.26
06	△06	ADD LOGO	Wang	2014.03.17

NOTES:

- MATERIAL:
 - Housing:High Temperature Thermoplastic UL94V-0; Color Black.
 - Terminal:Copper Alloy.
 - Nail:Stainless Steel
- SPECIALITY:
 - Rated current:2.0A
 - Rated voltage:30V
 - Contact Resistance:50mΩ MAX
 - Insulation Resistance:100MΩ MIN 100V DC
 - Dielectric withstanding voltage: 100V AC.
 - Solder ability:245±5℃, 5±0.5s.
 - Durability:5000 Cycles Min.
 - Operating condition:Temperature: -30℃~+80℃; Humidity: 80% R.H MAX

Ordering Information

Battery Series: 2BA 03 07 300 XXX -26

No. of PINS:03(3PIN)

Plating Number: 300:Pitch 3.00mm

Running number: XXX

Product Height: -26

PART No.	DIM A	DIM B	PART No.	DIM A	DIM B
2BA0307300450-26	4.50	3.00	2BA0307300600-26	6.00	4.50
2BA0307300500-26	5.00	3.50	2BA0307300620-26	6.20	4.70
2BA0307300550-26	5.50	4.00			

QUADRANT POINT (QP) TANGENCY POINT (TP) INTERSECTION POINT (IP) UNLESS OTHERWISE SPECIFIED, TOLERANCE: X. ±0.25 X.x ±0.20 X.xx ±0.15 ANGULAR ±3°		Singatron Enterprise Co., Ltd.	
TITLE: 3PIN BATTERY PH:3.00mm SMT TYPE WITH 2 POST DWN: Huang CHKD: 2012.09.26 APVD: Andy.L		PART NO.: 2BA0307300XXX-26 SCALE: 1:1 UNIT: mm SIZE: A3 SHEET: 1 OF 1 REV: 06	
CUSTOMER COPY			