



P.C.B. LAYOUT

料号说明:
 2BA04F-2565A1-XX 0B-SHR
 端子表面处理:
 01:全金1u"/0A:半金锡1u"
 03:全金3u"/0B:半金锡3u"
 05:全金5u"/0C:半金锡5u"
 08:全金8u"/0D:半金锡8u"
 10:全金10u"/0E:半金锡10u"
 15:全金15u"/0F:半金锡15u"
 30:全金30u"/0G:半金锡30u".

SPECIFICATION:
 1.CURRENT RATING:0.5A 50V AC/DC.
 2.CONTACT RESISTANCE:60mΩ MAX AT DC 20mA.
 3.INSULATION RESISTANCE:100MΩ MIN AT 500V DC.
 4.OPERATING TEMPERATURE RANGE:-25°C TO +85°C.
 5.MARKED "▼" ARE IMPORTANT DIMENSIONS.

Bill Of Materials:

No.	TITLE	MATERIAL	FINISH(OR COLOR)	NO
1	HOUSING	LCP+30%GF,UL94 V-0	BLACK	1
2	TERMINAL	C5210R-H,T=0.15mm	3u" GLOD PLATED	4
3	GROUND SLICE	BRASS(C2680R-H),T=0.20mm	TIN PLATED	2
4	GO TO SLICE	BRASS(C2680R-H),T=0.20mm	TIN PLATED	2

REV	ECN DESCRIPTION	DATE	CHANGE
A/1	整理图面及增加料号说明	2012-06-27	伍仕猛
A/2	修改弹高尺寸, 将1.74±0.20改为1.80±0.15	2015-08-27	陈礼明

UNLESS OTHERWISE SPECIFIED TOLERANCES		Singatron Enterprise Co., Ltd.	
DECIMALS:	ANGLES:	TITLE	4P电池座(2.5PH,6.5H)
X :±0.5	X :±2°	DWN	Word 04/26/2012 PART NO. 2BA04F-2565A1-030B-SHR
X.X :±0.3	X.X :±1°	CHKD	SCALE 1:1 UNIT: mm
X.XX :±0.2		APVD	SIZE: A3 SHEET:1 OF 1 REV:A2
CUSTOMER COPY			