



- NOTES:
1. WATERPROOF RATE: IP67  
IP67: IMMERSED IN 1M WATER FOR 30 MINUTES
  2. ELECTRICAL CHARACTERISTICS  
TEMPERATURE RANGE: -40°C TO +100°C  
CURRENT RATING: 10A
  3. DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC FOR ONE MINUTE
  4. SPECIFICATIONS: SEE "CIRCULAR SERIES SPECIFICATIONS."
  5. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
  6. GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING:

REV.	ECN NO.	OR DESCRIPTION	REVISED	DATE
A	PDR NO.:S101101-2B		Shown	2010.12.30
B	ECN NO.:S121109		YF	2014.03.27

E	LIQUID GLUE	1	N/A	BLACK
D	NUT	1	NYLON+33%GF	BLACK
C	GASKET	1	EPDM	BLACK
B	MALE PIN	3	BRASS	6u" GOLD PLATING OVER NICKEL PLATING
A	BODY	1	NYLON+33%GF	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
Singatron Enterprise Co., Ltd. 信登企業股份有限公司 CIRCULAR MIDDLE SIZE (SOLDER/LOCK TYPE) MALE CONN. MALE SPIN (10A)				
DECIMALS:		ANGLES:		
X	:±0.5	X	:±2°	
X.X	:±0.3	X.X	:±1'	
X.XX	:±0.2			
CHKD	Harten	SCALE: 2:1	UNIT: mm	
APVD	Quan	SIZE: A3	SHEET: 1 OF 1	REV: B

PIN ASSIGNMENTS  
FRONT VIEW

CUSTOMER COPY