



- NOTES:
1. WATERPROOF RATE: IP67
IP67: IMMersed IN 1M WATER FOR 30 MINUTES
 2. ELECTRICAL CHARACTERISTICS
TEMPERATURE RANGE: -40°C TO +100°C
CURRENT RATING: 5A
 3. SPECIFICATIONS: SEE "CIRCULAR SERIES SPECIFICATIONS."
 4. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
 5. GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING:
 6. FOR PANEL THICKNESS MAX OF 3.5mm

REV.	ECN NO.	OR DESCRIPTION	REVISED	DATE
A	PDR NO.: T101109-22A		Shown	2011.12.03
B	ECN NO.: S121109		YF	2014.03.27
C	ECN NO.: S202104-R12		LEI	2021.07.15

E	LIQUID GLUE	1	N/A	BLACK
D	NUT	1	NYLON+33%GF	BLACK
C	GASKET	1	EPDM	BLACK
B	MALE PIN	12	BRASS	6u" GOLD PLATING OVER NICKEL PLATING
A	BODY	1	NYLON+33%GF	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
Suzhou Singatron Auto Electronics CO., LTD. 苏州信誉汽车电子有限公司				
TITLE: CIRCULAR MIDDLE SIZE (SOLDER/LOCK TYPE)				
DECIMALS: ANGLES:				
X	:±0.5	X	:±2°	
X.X	:±0.3	X.X	:±1°	
X.XX	:±0.2			
DWG: LEI PART NO.: 2CM3002-W12300 CHKD: JF SCALE: 2:1 UNIT: mm APVD: JF SIZE: A3 SHEET: 1 OF 1 REV: C				
CUSTOMER COPY				