





REV	ECN NO	OR DESCRIPTION	REVISED	DATE
A		PDR NO.:S140217-10E	Wcky	2014.04.23



WATERPROOF RATE: IP67



BLACK	2
RED	1
WIRE COLOR	CONN.
PIN OUT	
CONN.	



Pin Assignments  
Front View

- NOTES:
- ELECTRICAL CHARACTERISTICS:
    - 1-1 CURRENT RATING: 10 AMPS.
    - 1-2 CONTACT RESISTANCE: 3 Ohm Max.
    - 1-3 INSULATION RESISTANCE: 100 Mohm Min. at 500VDC.
    - 1-4 BREAKDOWN VOLTAGE: 1000 VAC PER MINUTE.
  - ENVIRONMENTAL:
    - 2-1 OPERATING TEMPERATURE: -20°C TO +80°C.
    - 2-2 SEALING REQUIREMENTS: IP67.
    - 3. LIFE TEST: 1,000 CYCLES MIN.
  - OTHER GENERAL SPEC. TO REFER "CIRCULAR SERIES GENERAL SPEC".
  - FOR TECHNICAL DATA REFER TO YOUR LOCAL SINGATRON ELECTRONICS SALES OFFICE.
  - ALL DIMENSIONS ARE NOMINAL FOR REFERENCE ONLY UNLESS OTHERWISE STATED.
  - TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
  - GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING: .

G	CABLE	1	PVC UL2464 18#*2C+1(UV) OD=6.0	BLACK (PVC JACKET)
F	INNER MOLD	1	TPU	NATURAL
E	OVER MOLD	1	PVC	BLACK
D	O-RING	1	EPDM	BLACK
C	LOCK NUT	1	NYLON+33%GF	BLACK
B	FEMALE PIN	2	PHOSPHOR BRONZE	6u" GOLD PLATING OVER NICKEL PLATING
A	BODY	1	NYLON+33%GF	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
Singatron Enterprise Co., Ltd. 信登企業股份有限公司				
TITLE: CIRCULAR STANDARD SIZE (P67)				
FEMALE CONN. FEMALE PIN(T0A) LOCK TYPE				
DWN	Vicky	PART NO.2CT3004-W02477H		
CHKD	Harlen	SCALE 2:1	UNIT: mm	
APVD	Quon	SIZE: A3	SHEET: 1 OF 1	REV: A
CUSTOMER COPY				