



REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PDR NO.:C120430-7A~7B	Shawn	2012.06.20
B	ECN NO.S130725	YF	2014.08.13
C	ECN NO.:S141261	LIN	2015.04.07

- NOTES:
1. WATERPROOF RATE: IP67
IP67: IMMERSED IN 1M WATER FOR 30 MINUTES
 2. SEAL FOR CABLE OD: $\phi 4.0\text{mm} \sim \phi 6.5\text{mm}$
 3. SPECIFICATIONS: SEE "CIRCULAR SERIES SPECIFICATIONS".
 4. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
 5. GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING: **GREEN PART**
 6. ORDER INFORMATION:
2CT3033-WOX300H
02~03 - 2~3 PIN

B	2CT3033-W02300H		5A	22AWG~24AWG *2C
A	2CT3033-W03300H		5A	22AWG~24AWG *3C
	P/N:	Pin Assignments Front View	Current Rating	Recommended Cable AWG

G	LIQUID GLUE	1	N/A	BLACK
F	MALE PIN	*	HBI59-1.5B	6u" GOLD PLATING OVER NICKEL PLATING
E	BODY	1	NYLON+33%GF	BLACK
D	GASKET	1	SILICONE	BLACK
C	CLAMP RING	1	PC	BLACK
B	SEAL	1	EPDM	BLACK
A	SEALING NUT	1	PC	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES		Singatron Enterprise Co., Ltd. 信音企業股份有限公司		
DECIMALS: X : ±0.5 X.X : ±0.3 X.XX : ±0.2		TITLE CIRCULAR STANDARD SIZE (IP67) MALE CONN. MALE (2~3) PIN ASSEMBLY TYPE		
DWN	LIN	PART NO. 2CT3033-W0300H		A
CHKD	Yang	SCALE 2:1	UNIT: mm	REV: C
APVD	Harlen	SIZE: A3	SHEET: 1 OF 1	
CUSTOMER COPY				