



SPECIFICATIONS:

1. RATING: DC 20V 5.5A
2. INSERTION FORCE: 0.4Kg~3.0Kg
WITHDRAWAL FORCE: 0.4Kg~3.0Kg
3. INSULATION RESISTANCE BETWEEN ANY ADJACENT TERMINALS SHALL NOT BE LESS THAN 100 MEGOHMS BY 500 VOLTS MEGGER.
4. JACK SHALL WITHSTAND 500 VOLTS BETWEEN ANY ADJACENT TERMINAL FOR ONE MINUTE.
5. CONTACT RESISTANCE SHALL NOT EXCEED 0.03 OHMS.
6. JACK SHALL WITHSTAND 5,000 CYCLES OF INSERTION AND WITHDRAWAL WITH TESTING PLUG, AND CONTACT RESISTANCE SHALL NOT EXCEED 0.06 OHMS.
7. MEASURING CONDITION:
TEMPERATURE: FROM 5°C TO 35°C.
RELATIVE HUMIDITY: FROM 40% TO 85%.
8. PACKING: TAPE&REEL
9. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
10. HALOGEN FREE PRODUCT IDENTIFICATION MARK ON PRODUCT:
11. HALOGEN PRODUCT IDENTIFICATION LABEL ON PACKAGING:
12. PRINTED DATE CODE "YMMDD" ON TOP OF CONNECTOR.



NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
G	GROUNDING SPRING	1	SUS 0.1t	
F	SHIELDING	1	SPCC 0.3t	NICKEL PLATING
E	TERMINAL	1	COPPER ALLOY 0.3t	SILVER PLATING
D	CONTACT PIN	1	BRASS Ø2.5	NICKEL PLATING
C	SHUNT	1	BRASS 0.3t	SILVER PLATING
B	TIP SPRING	1	COPPER ALLOY 0.3t	SILVER PLATING
A	BODY	1	NYLON-10T+30%GF	BLACK COLOR

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS: ANGLES:

X :±0.5 X :±2
 X.X :±0.3 X.X :±1'
 X.XX :±0.2

REV.	ECN NO	OR DESCRIPTION	REVISED	DATE
A	PDR NO:1090109-8A	ADD A TYPE	HAIHUA	2009.4.23
B	CS 重新審核標準 品質 規格 變更 通知 書	CHANGSHENG		10.04.20
C	ECN NO: C100404	Add Dimension	LONGJIANG	2010.12.27
D	ECN: C110345-4	MODIFY DIMENSION	Haijin	2012.01.04

Singatron Enterprise Co., Ltd.
 信登企業股份有限公司

TITLE: DC POWER JACK

DWN	DATE: 2012.01.04	PART NO. ZDC-G328-B06	SCALE: 4:1	UNIT: mm	REV: D
CHKD	DATE: 2012.01.04		SIZE: A3	SHEET: 10F1	
APVD	DATE: 2012.01.04		CUSTOMER COPY		