



SPECIFICATIONS:

- ELECTRICAL CHARACTERISTICS:**
 - VOLTAGE RATING: 30V AC OR 42V DC;
 - CURRENT RATING: 9A
 - CONTACT RESISTANCE: 30mΩ MAX.(INITIAL)
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE
 - INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC
- MECHANICAL CHARACTERISTICS:**
 - INSERTION FORCE :3.0 KG Max.
 - WITHDRAWAL FORCE : 0.3~3.0 KG.
- LIFE TEST: 5,000 CYCLES MIN.
- TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
- HALOGEN FREE PRODUCT IDENTIFICATION MARK ON JACK:
- HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING:
- FOR REFLOW SOLDERING LEAD-FREE PROCESS.
- PRINTED DATE CODE "YYMMDD" ON TOP OF CONNECTOR.



REV	ECN NO.	OR DESCRIPTION	REVISED	DATE
A	PDR NO. 1110803-4A		Springw4	2012.02.17
B	ECN NO: S1209955		SEAN	2012.12.03

REV	ECN NO.	OR DESCRIPTION	REVISED	DATE
A	PDR NO. 2DC3035-000111F		Springw4	2012.02.17
B	ECN NO: S1209955		SEAN	2012.12.03

DECIMALS:	ANGLES:
X :±0.5	X :±2°
XX :±0.3	X.X :±1°
XXX :±0.2	

REV	ECN NO.	OR DESCRIPTION	REVISED	DATE
A	PDR NO. 2DC3035-000111F		Springw4	2012.02.17
B	ECN NO: S1209955		SEAN	2012.12.03

Singatron Enterprise Co., Ltd.
信亨企業股份有限公司

TITLE: DC JACK
DWN: SEAN
CHKD: TOM
APVD: MAX
PART NO: 2DC3035-000111F
SCALE: 4:1
SIZE: A3
SHEET: 1 OF 1
RBY: B