

REV.	ECN.NO.	DATE
A	RELEASED	10/11-'07
E	Modify Drawing	09/24-'15
F	Change How To Order	01/24-'17

NOTES:

***Material**

Housing: LCP,UL 94V-0Rated;Color:Black.
 Shield: Brass.
 Plating: Ni(40u" Min.) Plating.
 Contact: Brass.
 Plating: Au plating on contact area;
 Sn(100u" Min.) plating on solder tail;
 Ni(40u" Min.) underplating overall.

***Electrical Specification**

Operation Voltage: 40 VAC max.
 Current Rating: 0.5 Ampere per contact
 Contact Resistance: 30 mΩ max.
 Insulation Resistance: 100 MΩ min.
 Dielectric Withstanding Voltage: 500 VDC

***Environmental**

Operating Temperature: -20°C to +85°C

***How To Order**

2DPP-020-R3S-00
 └── Blank:Tray R:Reel
 └── Au F:>0.8u" 5:15u" 3:30u"
 └── Number of Contacts
 └── Series NO.

Tolerance Unless Otherwise Specified	
.X	± 0.35
.XX	± 0.25
.XXX	± 0.15
Angle	± 3°

Singatron Enterprise Co., Ltd.			
TITLE	DisplayPort Receptacle (Female) SMT Type		
DWN	Laliu01/27-'17	PART NO.	2DPP-020-R3S-00
CHKD	Sharon01/27-'17	SCALE 1:1	UNIT: mm
APVD	Jason01/27-'17	SIZE: A3	SHEET:1 OF 1 REV: F
CUSTOMER COPY			

