

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PDR NO:S180425-7A	Chensong	2018.09.08
B	ECN NO: L202301-001	EVEN	2023.02.20

- ELECTRICAL CHARACTERISTICS**
CURRENT RATING : 1.5 AMP DC
VOLTAGE RATING: 40 V DC
CONTACT RESISTANCE :20 MILLIOHMS MAX.
DIELECTRIC WITHSTANDING VOLTAGE : 500 V AC MIN.
INSULATION RESISTANCE : 1000 MEGAOHMS MIN.
- MECHANICAL**
MATING FORCE:4.5Kgf MAX.
UNMATING FORCE:1.0-4.0 Kgf
- ENVIRONMENTAL**
OPERATING TEMPERATURE: -55°C ~ +85°C
STORAGE TEMPERATURE:-55°C ~ +105°C
- HOW TO ORDER:**

NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
E	COBBER PILLAR	2	Alloy	NICKEL and NIN MIN 60u"MIN
D	COVER	1	PBT	WHITE
C	TERMINAL	29	COPPER ALLOY T=0.30	G/F Au ON MATING AREA, 100u"MIN IN PLATED ON SOLDERING 50u" NICKEL UNDER PLATING OVERALL
B	SHELL	1	SPCC T=0.50	NICKEL 60u"MIN
A	HOUSING	1	PBT	WHITE

UNLESS OTHERWISE SPECIFIED TOLERANCES		 信音科技(香港)有限公司			
DECIMALS: X	:±0.50	ANGLES: X	:±2°	TITLE	DVI(24+5) PIN CONNECTOR, VERTICAL
X.X	:±0.30	X.X	:±1°	DWN	EVEN 2023.02.20 PART NO.2DS3Y62-005112H
X.XX	:±0.2			CHKD	SCALE 4:1 UNIT: mm
		APVD	TERESA 2023.02.20	SIZE: A3	SHEET:1 OF 1 REV: B
CUSTOMER COPY					

