


REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PDR No.:T150514-5A	Wenshuo	2015.10.19
B	ECN No.:S151029-C	Ken	2016.1.22
C	ECN No.:S160744-C	Ken	2016.9.28
D	ECN No.:S161238-C	Ken	2017.02.24
E	ECN No.:S202001-Q02	Xuehua	2020.1.10

- SPECIFICATIONS:
- ELECTRICAL CHARACTERISTICS:
 - RATING:20V 3A
 - CONTACT RESISTANCE:30mΩ MAX.(INITIAL)
 - DIELECTRIC WITHSTANDING VOLTAGE:250V AC FOR ONE MINUTE.
 - INSULATION RESISTANCE:100MΩ MIN. MEASURED BY 500V DC.
 - MECHANICAL CHARACTERISTICS:
 - INSERTION FORCE:3.5 KG MAX.
 - WITHDRAWAL FORCE:0.5~3.5 KG.
 - LIFE TEST:5000 CYCLES MIN.
 - OTHER GENERAL SPEC. TO REFER "2DW3057-005111F SPEC".
 - TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
 - HALOGEN FREE PRODUCT IDENTIFICATION MARK ON JACK: ●
 - HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING: ⊗
 - PRINTED DATE CODE "YYMMDD" ON TOP OF CONNECTOR.



LABEL

N	ACETATE CLOTH TAPE	1	W5*10.12	BLACK
M	UV GLUE	1	8860	WHITE
L	ADHESIVE TAPE	1	3M 9448 7.2*5.0	WHITE
K	鋁箔導電膠	1	W5.5*L23*Ø0.15	WHITE
J	ACETATE CLOTH TAPE	1	W8*L14*Ø0.12	BLACK
H	LABEL	1	20*6	WHITE
G	CORE	1	R5ASH7.5*5.3*8C5E2.8	BLACK
F	HEAT SHRINK TUBE	2	FOLYOLIFEN Ø2.5mm(125°,300V)	BLACK
E	HEAT SHRINK TUBE	2	FOLYOLIFEN Ø3.5mm(125°,300V)	BLACK
D	WIRE	2	UL10368 26AWG	BLACK
C	WIRE	2	UL10368 26AWG	RED
B	CONNECTOR	4	TERMINAL:PHOSPHOR BRONZE	GOLD PLATING
		1	HOUSING:NYLON66 UL 94V-0	WHITE
A	DC POWER JACK	1	TO SEE SINGATRON DC JACK P/N:2DC3057-000111F	

NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES			Singatron Enterprise Co., Ltd. 信音企業股份有限公司	
DECIMALS:		ANGLES:	TITLE: DC POWER JACK+WIRE	
X	:±0.5	X	:±2°	DWN Xuehua PART NO.2DW3057-005111F
X.X	:±0.3	X.X	:±1°	CHKD Ron SCALE:-- UNIT: mm
X.XX	:±0.2			APVD Lussen SIZE: A3 SHEET:1 OF 1 REV:E

CUSTOMER COPY