




REV	ECN NO	OR DESCRIPTION	REVISED	DATE
A	PDR NO.:S140519-6B		Vicky	2014.05.29
B	ECN NO.:S151212-C		Vicky	2016.03.17
C	ECN NO.:S160801-R		Vicky	2016.08.01



CONN.1	WIRE COLOR	PIN OUT
9	BLACK	9
8	RED	8
7	BLUE	7
6	YELLOW	6
5	GREEN	5
4	WHITE	4
3	GREEN(16#)	3
2	BLUE(16#)	2
1	YELLOW(16#)	1



- NOTES:
1. WATERPROOF RATE: IP65
  2. CURRENT RATING: 10A+5A
  3. CONTACT RESISTANCE: 3 Ohm Max.
  4. HI-POT TEST 800V AC, 5mA(1SEC)
  5. INSULATION RESISTANCE: 30Mohm MIN. BY 500V DC
  6. SPECIFICATIONS:SEE "E-BIKE SERIES SPECIFICATIONS".
  7. TO CONFORM TO THE SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
  8. GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING:

NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
A	BODY	2	PA66+GF	BLACK
B	FEMALE PIN	9	Phosphor Bronze	1~3u" GOLD PLATING OVER NICKEL PLATING
C	OVER MOLD	1	HYTREL	BLACK
D	CABLE	1	16#*3C+24#*6C	OD5.9 BLACK(PVC JACKET)
E	INNER MOLD	2	PVC	BLACK
F	SHRINK TUBE	12	Ø1.5mm 300V	BLACK
G	MALE PIN	9	BRASS	1~3u" GOLD PLATING OVER NICKEL PLATING
H	CAP	1	NYLON	WHITE
I	OVER MOLD	1	TPU	BLACK

DECIMALS:	ANGLES:	TITLE
X :±0.5	X :±2°	E-BIKE SERIES 180° 9 PIN CONN.
X.X :±0.3	X.X :±1'	
X.XX :±0.2		

Singatron Enterprise Co., Ltd.  
信譽企業股份有限公司

PART NO. 2EBB3004-W09712H

SCALE 2:1 UNIT: mm

SIZE: A3 SHEET: 1 OF 1 REV: C

CUSTOMER COPY