




REV	ECN NO	OR DESCRIPTION	REVISED	DATE
A	PDR NO.:S150520-5A	Lin	2015.05.15	
B	ECN NO.:S151212-C	Wcky	2016.03.17	
C	ECN NO.:S160801-R	Wcky	2016.08.01	



9	BLACK	9
8	RED	8
7	BLUE	7
6	YELLOW	6
5	GREEN	5
4	WHITE	4
3	GREEN(16#)	3
2	BLUE(16#)	2
1	YELLOW(16#)	1
CONN.1 WIRE COLOR		CONN.2
PIN OUT		



- NOTES:
1. WATERPROOF RATE: IP65
  2. CURRENT RATING: 10A+5A
  3. CONTACT RESISTANCE: 3 Ohm Max.
  4. HI-POT TEST 800V AC, 5mA(1SEC)
  5. INSULATION RESISTANCE: 30Mohm MIN. BY 500V DC
  6. SPECIFICATIONS:SEE "E-BIKE SERIES SPECIFICATIONS".
  7. TO CONFORM TO THE SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
  8. GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING:

NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
A	BODY	2	PA66+GF	BLACK
B	FEMALE PIN	9	Phosphor Bronze	1~3u" GOLD PLATING OVER NICKEL PLATING
C	OVER MOLD	1	HYTREL	BLACK
D	CABLE	1	16#*3C+24#*6C	BLACK(PVC JACKET)
E	INNER MOLD	2	PVC	BLACK
F	SHRINK TUBE	12	Ø1.5mm 300V	BLACK
G	MALE PIN	9	BRASS	1~3u" GOLD PLATING OVER NICKEL PLATING
H	CAP	1	NYLON	NATURAL
I	OVER MOLD	1	TPU	BLACK

DECIMALS:	ANGLES:	TITLE
X :±0.5	X :±2°	E-BIKE SERIES 180° 9 PIN CONN.
X.X :±0.3	X.X :±1°	
X.XX :±0.2		