



■ SPECIFICATIONS

- Voltage Rating : 250V AC/DC
- Current Rating : 1A AC/DC
- Withstanding Voltage : 500V AC/minute
- Insulation Resistance : 1000M Ω min
- Temperature Range : - 55°C to + 85°C
- Contact Resistance : 20m Ω max

■ FFC/FPC CONNECTOR

- Part No. : 2FF1155A-XX
- Poles : 4-30(Straight , Normality Contacts)
- Material : Contact : Phos. Bronze, Tin Plated
Base : PBT UL94V-0
- Q' ty : 1000 pcs/Tube Pack

Applicable FPC/FFC T=0.30±0.05

Poles	Part No.	Dimensions (mm)			Poles	Part No.	Dimensions (mm)		
		A	B	C			A	B	C
4	2FF1155A-04	3.75	6.30	8.40	18	2FF1155A-18	21.25	23.80	25.90
5	2FF1155A-05	5.00	7.55	9.65	19	2FF1155A-19	22.50	25.05	27.15
6	2FF1155A-06	6.25	8.80	10.90	20	2FF1155A-20	23.75	26.30	28.40
7	2FF1155A-07	7.50	10.05	12.15	21	2FF1155A-21	25.00	27.55	29.65
8	2FF1155A-08	8.75	11.30	13.40	22	2FF1155A-22	26.25	28.80	30.90
9	2FF1155A-09	10.00	12.55	14.65	23	2FF1155A-23	27.50	30.05	32.15
10	2FF1155A-10	11.25	13.80	15.90	24	2FF1155A-24	28.75	31.30	33.40
11	2FF1155A-11	12.50	15.05	17.15	25	2FF1155A-25	30.00	32.55	34.65
12	2FF1155A-12	13.75	16.30	18.40	26	2FF1155A-26	31.25	33.80	35.90
13	2FF1155A-13	15.00	17.55	19.65	27	2FF1155A-27	32.50	35.05	37.15
14	2FF1155A-14	16.25	18.80	20.90	28	2FF1155A-28	33.75	36.30	38.40
15	2FF1155A-15	17.50	20.05	22.15	29	2FF1155A-29	35.00	37.55	39.65
16	2FF1155A-16	18.75	21.30	23.40	30	2FF1155A-30	36.25	38.80	40.90
17	2FF1155A-17	20.00	22.55	24.65					

TOLERANCE	LTR	REVISION RECORD	DATE
.0	±0.3	ECR	RoHS Compliant 06/04/01
.00	±0.2	ECR	200809-012 08/09/17
.000	±0.1	ECR	200909-011 09/09/25
ALL	±		
ANGLE			
0°	±		
.0°	±		

Singatron Enterprise Co., Ltd.				
TITLE	1.25mm NON-ZIF Connectors Single Beam Contact Style			
DWN	林宗	PART NO. 2FF1155A-XX		
CHKD	黄科源	SCALE 1:1	UNIT: mm	④
APVD	张育瑞	SIZE: A3	SHEET: 1 OF 1	REV: a2
CUSTOMER COPY				