



■ SPECIFICATIONS

- △ Current Rating : 3A AC/DC
- △ Voltage Rating : 250V AC/DC
  - Withstanding Voltage : 500V AC/minute
  - Insulation Resistance : 1,000MΩ min
- △ Temperature Range : - 25°C to + 85°C
- △ Contact Resistance : 30mΩ max

■ FFC/FPC CONNECTOR

- Part No. : 2FF1160R-XX
- ① Poles : 02~26(Right Angle)
- RoHS Compliant 2002/95/EC
- Material :
  - 1.Contact : Phos. Bronze, Tin Plated
  - 2.Base : PBT UL94V-0
- Q' ty : 1,000pcs./Bag

Poles	Dimensions (mm)		
	A	B	C
2	2.54	10.54	8.43
3	5.08	13.08	10.97
4	7.62	15.62	13.51
5	10.16	18.16	16.05
6	12.70	20.70	18.59
7	15.24	23.24	21.13
8	17.78	25.78	23.67
9	20.32	28.32	26.21
10	22.86	30.86	28.75
11	25.40	33.40	31.29
12	27.94	35.94	33.83
13	30.48	38.48	36.37
14	33.02	41.02	38.91
15	35.56	43.56	41.45
16	38.10	46.10	43.99
17	40.64	48.64	46.53
18	43.18	51.18	49.07
19	45.72	53.72	51.61
20	48.26	56.26	54.15
21	50.80	58.80	56.69
22	53.34	61.34	59.23
23	55.88	63.88	61.77
24	58.42	66.42	64.31
25	60.96	68.96	66.85
26	63.50	71.50	69.39

TOLERANCE	LTR	REVISION RECORD	NAME	DATE
.0	±0.30	△ XXX	XXX	XXXX/XX/XX
.00	±0.20	△ ECR 200811-003	XXX	2008/11/03
.000	±0.10	△ ECR 201006-001	王誠賢	2010/06/02
ANGLE		△ 增加剖面圖	吳弘文	2014/04/07
0°	±1°	△ 修定電氣規格	吳弘文	2014/07/22
.0°	±	△		
SHEET	1/1	△		

Singatron Enterprise Co., Ltd.				
TITLE	2.54mm NON-ZIF FPC Connectors			
DWN	吳弘文	PART NO. 2FF1160R-XX		
CHKD	周慈雲	SCALE 1:1	UNIT: mm	⊕
APVD	張育瑞	SIZE: A3	SHEET: 1 OF 1	REV: a5
CUSTOMER COPY				