



Recommended PCB Layout
 <TOP VIEWS> TOLERANCE: ±0.05

REV.	ECN NO.	OR DESCRIPTION	REVISED	DATE
T	PDR NO.20070102-1		LULU	2007.01.07
A	PDR RELEASE		LULU	2007.01.18

- SPECIFICATIONS**
- OPERATING CURRENT: 0.5A MAX.
 - DIELECTRIC WITHSTANDING VOLTAGE:
 - 3.500volts AC BETWEEN ADJACENT TERMINAL (UNMATE)
 - 4.300volts AC BETWEEN ADJACENT TERMINAL(MATE)
 - OPERATION TEMPERATURE: -25°C TO +85°C
 - INSULATION RESISTANCE:
 - 6.100Mohm MIN.(UNMATED);10Mohm MIN.(MATED)
 - 7.TO CONFORM TO THE "SE-01-001" & "RHS DIRECTIVE"
 - GREEN PRODUCT IDENTIFICATION LABEL IN PACKING: **G.P. PASS**
 - SOLDER HEAT RESISTANCE : 260°C 10 SECS.
 - 10 SEE " ZHE1511 SERIES SPEC."

- ZHE1511-000311
- 1: PACKAGE
 - 1: TAPE & REEL
 - 1: BODY COLOR
 - 1: BLACK
 - CONTACT PLATING
 - 3: 30μ" GOLD PLATED IN CONTACT AREA AND GOLD FLASH PLATED IN SOLDER AREA
 - OVER 50μ" NICKEL UNDERPLATING

NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
C	CONTACT	19	COPPER ALLOY	30μ" GOLD PLATED IN CONTACT AREA AND GOLD FLASH PLATED IN SOLDER AREA OVER 50μ" NICKEL UNDERPLATING
B	SHELL	1	COPPER ALLOY	NICKLE PLATING
A	HOUSING	1	HIGH TEMPERATURE THERMOPLASTIC UL 94V-0	BLACK COLOR

DECIMALS:	ANGLES:
X : ±0.5	X : ±2°
XX : ±0.3	XX : ±1°
XXX : ±0.2	

TITLE	HDMI RECEPTACLE,TYPE C PITCH 0.40 SMT TYPE
DRAWN	信亨企業股份有限公司
CHKD	PART NO.ZHE1511-000311
APVD	SCALE:3/1
	UNIT: mm
	SHEET:1 OF1
	REV: A

CUSTOMER COPY