



SPECIFICATIONS:

1. ELECTRICAL CHARACTERISTICS:
 - 1-1. CURRENT RATING: 0.5 AMP.
 - 1-2. VOLTAGE RATING: 30V.
 - 1-3. CONTACT RESISTANCE: 30mΩ MAX.
 - 1-4. INSULATION RESISTANCE: 100MΩ MIN. @ 500V DC.
 - 1-5. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
2. MECHANICAL CHARACTERISTICS:
 - 2-1. INSERTION FORCE: 44.1N(4.5kgf) MAX
 - 2-2. WITHDRAWAL FORCE: 9.8~39.2N(1.0~4.0kgf).
3. LIFE TEST: 10,000 CYCLES.
4. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPECIFICATION
5. HALOGEN FREE PRODUCT IDENTIFICATION LOGO ON PACKAGING:
6. FOR REFLOW SOLDERING LEAD-FREE PROCESS.
7. PACKAGING: TAPE&REEL

RECOMMENDED PCB LAYOUT(T:1.2±0.05mm):
COMPONENT SIDE(TOL:±0.05)(TOP VIEW)

REV.	ECN NO.	OR DESCRIPTION	REVISED	DATE
A	PDR NO.S170128-2A		Charles	2015.05.08
B	ECN NO.S170307-C		YUREN	2017.5.31
C	ECN NO.L180042		EVEN	2018.12.21

D	CONTACT	19	COPPER ALLOY	GOLD 5μ" PLATED ON CONTACT AREA
C	SHELL	1	STAINLESS STEEL	NICKEL PLATED
B	TOP COVER	1	LCP UL 94V-0	BLACK
A	HOUSING	1	LCP UL 94V-0	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
Singatron Enterprise Co., Ltd. 信音企業股份有限公司				
TITLE: HDMI A TYPE R/A DIP RVS OFFSET 0.4H				
DWN: 2018.12.21 PART NO. 2HE3Y62-000111F				
CHKD: SCALE 1/1 UNIT: mm				
APVD: 2018.12.21 SIZE: A3 SHEET: 1 OF 1 REV: C				

CUSTOMER COPY