

| REV. | ECN NO OR DESCRIPTION | REVISED | DATE |
|------|-----------------------|---------|------------|
| A | PDR RELEASE | IVY-C | 2013.11.05 |
| B | ECN NO:L202106-C06 | EVEN | 2021.08.17 |

SPECIFICATIONS:

- CURRENT RATING: 1.5 AMP MAX.
- VOLTAGE RATING: 150 VAC MAX.
- INSULATION RESISTANCE: 1000M OHMS MIN.
- DIELECTRIC WITHSTANDING VOLTAGE: 1000 VAC 60Hz 1 MINUTE.
- DURABILITY: 5,000 CYCLES MIN.
- OPERATING TEMPERATURE: -30°C TO +70°C.
- OTHER GENERAL SPEC. TO REFER "2RJ1544-010211F SPEC".
- TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
- HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING:
- PACKAGE: SEE "2RJ1544-010211F" PACKAGE.
- FOR REFLOW SOLDERING LEAD-FREE PROCESS.
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.



PART NO.

2RJ1544-010211F

LED
1. WITH LED

SUFFIX: HALOGEN FREE

PACKAGE

1: TAPE & REEL Δ

HOUSING COLOR

1: BLACK

CONTACT AREA PLATING

2: 6u" GOLD PLATED ON CONTACT AREA,
TIN PLATED ON SOLDER AREA

| | | | |
|----|-------------|-----|--------------------------------------|
| E | INK | | BLACK |
| D | LED | 2 | YELLOW/GREEN TIN PLATED |
| C | SHELL | 1 | BRASS NICKEL |
| B | CONTACT | 8 | PHOSPHOR BRONZE SEE PART NO. |
| A | HOUSING | 1 | HIGH TEMP PLASTIC, UL 94V-0 BLACK |
| NO | DESCRIPTION | QTY | MATERIAL PLATING & COLOR |

UNLESS OTHERWISE SPECIFIED TOLERANCES



信音科技(香港)有限公司

| | | | | |
|------------|----------|-------|--|-------------------------------|
| DECIMALS: | ANGLES: | TITLE | RJ45 JACK, SIDE ENTRY, LED, WITH SHELL | |
| X :±0.5 | X :±2° | DWN | EVEN 2021.08.17 | PART NO. 2RJ1544-010211F |
| X.X :±0.3 | X.X :±1° | CHKD | SCALE 1:1 | UNIT: mm |
| X.XX :±0.2 | | APVD | ANGELA2021.08.17 | SIZE: A3 SHEET: 1 OF 1 REV: B |

CUSTOMER COPY

