

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	ECN NO:S180801-0-3	PAN	2018.09.10
B	ECN NO:L202009-C05	EVEN	2020.11.25

**SPECIFICATIONS:**

- VOLTAGE RATING: 150 VAC MAX.
- CURRENT RATING: 1.5 AMP MAX.
- INSULATION RESISTANCE: 1000M OHMS MIN. AT 500 VDC.
- DIELECTRIC WITHSTANDING VOLTAGE: 1000 VAC 60Hz 1 MINUTE.
- DURABILITY: 5000 CYCLES .
- OPERATING TEMPERATURE: -30°C TO +70°C.
- OTHER GENERAL SPEC. TO REFER "2RJ1622 SERIES SPEC".
- TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
- HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING:
- PACKAGE: SEE "2RJ1622 SERIES" PACKAGE.
- FOR REFLOW SOLDERING LEAD-FREE PROCESS.
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.



**PART NO.**

**2RJ1622-000111F**

**SUFFIX: HALOGEN FREE**

**PACKAGE**  
1: TAPE AND REEL

**HOUSING COLOR**  
1: BLACK

**CONTACT AREA PLATING**  
1: GOLD FLASH ON CONTACT AREA,  
TIN PLATING ON SOLDER AREA.

F	CAP	1	HIGH-TEMP. THERMO-PLASTIC, UL 94V-0	BLACK
E	MYLAR	1	KAPTON FILM	YELLOW
D	INK	-		BLACK
C	SHIELD	1	STAINLESS STEEL	NICKEL
B	CONTACT	8	COPPER ALLOY	SEE PART NO.
A	HOUSING	1	HIGH-TEMP. THERMO-PLASTIC, UL 94V-0	BLACK

NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES		信音科技(香港)有限公司		
DECIMALS:	ANGLES:	TITLE	RJ45 JACK, W/SHIELD, R/A, DIP TYPE	
X :±0.5	X :±2°	DWN	EVEN 2020.11.25 <b>PART NO. 2RJ1622-000111F</b>	
X.X :±0.3	X.X :±1°	CHKD	SCALE 3/1 UNIT: mm	
X.XX :±0.2		APVD	ANGELA2020.11.25	SIZE: A3 SHEET: 1 OF 1 REV: B
<b>CUSTOMER COPY</b>				

F  
E  
D  
C  
B  
A

1 2 3 4 5 6 7 8

