

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PDR RELEASE	EVEN	2017.04.12
B	ECN NO: L180031	EVEN	2018.12.07
C	ECN NO: L190085	IVY-C	2019.10.30
D	ECN NO: L202107-C01	EVEN	2021.08.20

SPECIFICATIONS:

- VOLTAGE RATING: 150 VAC MAX.
- CURRENT RATING: 1.5 AMP MAX.
- INSULATION RESISTANCE: 1000M OHMS MIN. AT 500 VDC.
- DIELECTRIC WITHSTANDING VOLTAGE: 1000 VAC 60Hz 1 MINUTE.
- DURABILITY: 5000 CYCLES .
- OPERATING TEMPERATURE: -30°C TO +70°C.
- TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
- HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING:
- PACKAGE: SEE "2RJ1622-001111F" PACKAGE.
- FOR REFLOW SOLDERING LEAD-FREE PROCESS.
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.
- OTHER GENERAL SPEC. TO REFER "2RJ1622 SERIES SPEC".



PART NO.

2RJ1622-001111F

SUFFIX: HALOGEN FREE

PACKAGE

1: TAPE AND REEL

HOUSING COLOR

1: BLACK

CONTACT AREA PLATING

1: GOLD FLASH ON CONTACT AREA,
100~200u" TIN PLATING ON SOLDER AREA.
30~80u" MIN. NICKEL UNDERPLATED OVERALL

D	MYLAR	1	KAPTON FILM	YELLOW
C	SHIELD	1	SUS201	NICKEL 30~80u"
B	CONTACT	8	C5210	SEE PART NO.
A	HOUSING	1	PA10T UL 94V-0	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR

UNLESS OTHERWISE SPECIFIED TOLERANCES

信音科技(香港)有限公司

DECIMALS:	ANGLES:	TITLE	RJ45 JACK, W/SHIELD, R/A, DIP TYPE	
X :±0.5	X :±2°	DWN	EVEN 2021.08.20	PART NO. 2RJ1622-001111F
X.X :±0.3	X.X :±1°	CHKD	SCALE 3/1	UNIT: mm
X.XX :±0.2		APVD	ANGELA2021.08.20	SIZE: A3 SHEET: 1 OF 1 REV: D

CUSTOMER COPY

