

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PDR RELEASE	IVY-C	2016.04.07
B	ECN NO: L190008	IVY-C	2019.09.26
C	ECN NO: L202203-C08	EVEN	2022.04.26

SPECIFICATIONS:

- VOLTAGE RATING: 150 VAC MAX.
- CURRENT RATING: 1.5 AMP MAX.
- INSULATION RESISTANCE: 1000MΩ MIN. AT 500V DC
- DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC 60Hz 1 MINUTE.
- OPERATING TEMPERATURE: -30°C TO +70°C.
- TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
- HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING:
- PACKAGE: SEE "2RJ1755-000X11F" PACKAGE.
- FOR REFLOW SOLDERING LEAD-FREE PROCESS.
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.
- DURABILITY: 5000 CYCLES.
- OTHER GENERAL SPEC. TO REFER "2RJ1755-000X11F SPEC".

PART NO.

2RJ1755-000X11F

SUFFIX: HALOGEN FREE

PACKAGE
1: TAPE & REEL

HOUSING COLOR
1: BLACK

CONTACT PLATING

1: GOLD FLASH ON CONTACT AREA,
50u" MIN MATTE TIN PLATING ON SOLDER AREA
30u" MIN NICKEL UNDERPLATED OVERALL

2: 30u" GOLD ON CONTACT AREA,
50u" MIN MATTE TIN PLATING ON SOLDER AREA
30u" MIN NICKEL UNDERPLATED OVERALL

VIEW A SCALE 5:1

FOOLPROOF DESIGN(2x)

MATE RJ45 PLUG

E	COVER	1	LCP UL 94V-0	BLACK COLOR
D	STOPPLE	2	LCP UL 94V-0	BLACK COLOR
C	CONTACT	8	PHOSPHOR BRONZE	SEE PART NO.
B	SHELL	1	STAINLESS STEEL	50u" NICKEL
A	HOUSING	1	PA10 UL 94V-0	BLACK COLOR
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR

UNLESS OTHERWISE
SPECIFIED TOLERANCES

DECIMALS: ANGLES:
X :±0.5 X :±2°
X.X :±0.3 X.X :±1°
X.XX :±0.2



信音科技(香港)有限公司

TITLE	RJ45 PHONE JACK		
DWN	EVEN 2022.04.26	PART NO.	2RJ1755-000X11F
CHKD		SCALE:1:1	UNIT: mm
APVD	ANGELA2022.04.26	SIZE: A3	SHEET:1 OF 1

CUSTOMER COPY