


SPECIFICATIONS:

- ELECTRICAL CHARACTERISTICS:
 - CURRENT RATING: 1.5A MAX.
 - VOLTAGE RATING: 150V MAX.
 - CONTACT RESISTANCE: 50mΩ MAX.(INITIAL), 100mΩ MAX.(AFTER LIFE TEST).
 - INSULATION RESISTANCE: 100MΩ MIN.
- MECHANICAL CHARACTERISTICS:
 - DURABILITY: 5000 CYCLES.
 - INSERTION FORCE: 2.1kg MAX. WITH LATCH DEPRESSED.
 - WITHDRAWAL FORCE: 3kg MIN. WITH LATCH DEPRESSED.
 - OPERATING TEMPERATURE: -30°C ~ +70°C.
- MARKING: MARK "S" INSIDE OF THE CONNECTOR.
- PACKAGING : TAPE & REEL.
- TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
- HALOGEN FREE PRODUCT IDENTIFICATION
- MARK ON PRODUCT:
 - HALOGEN FREE PRODUCT IDENTIFICATION LOGO ON THE PACKAGING:
 - FOR REFLOW SOLDERING LEAD-FREE PROCESS.
 - PRINTED DATE CODE "YY MM DD" ON TOP OF THE CONNECTOR.



NODE	COLOR
A1(+)	A2(-)
A1(+)	A2(-)
B1(+)	B2(-)
AMBER	B1+B2
	B2

NO.	DESCRIPTION	QTY	MATERIAL
F	LED	1	AMBER
E	LED	1	GREEN
D	STOP	2	LCP
C	SHELL	1	STAINLESS STEEL T=0.25
B	8P8C CONTACT	8	PHOSPHOR BRONZE T=0.25
A	BODY	1	LCP

UNLESS OTHERWISE SPECIFIED TOLERANCES		TITLE	
DECIMALS:	ANGLES:	RJ45 JACK	
X : ±0.5	X : ±2°	DWN	PART NO. 2RJ3054-188211F
X.X : ±0.3	X.X : ±1°	CHKD	JAMES SCALE 4:1 UNIT: mm
X.XX : ±0.2		APVD	BOYE SIZE: A3 SHEET: 1 OF 1 REV: B

Singatron Enterprise Co., Ltd.
信智企業股份有限公司

CUSTOMER COPY

REV.	ECN NO. OR DESCRIPTION	REVISED	DATE
A	PDR NO:T150326-4A	ALLEN	2015.08.25
B	EGR NO:S151014-E	ALLEN	2015.10.19