



REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PDR RELEASE	Even	2013.05.03
B	ECN NO:L130091	IVY-C	2013.11.11
C	ECN NO:L130154	IVY-C	2013.12.20
D	ECN NO:L140074	IVY-C	2014.07.11
E	ECN NO: L202109-C03	EVEN	2022.01.12

- SPECIFICATIONS:**
- VOLTAGE RATING: 150 VAC MAX.
 - CURRENT RATING: 1.5 AMP MAX.
 - INSULATION RESISTANCE: 500M OHMS MIN. AT 500 VDC.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC 60Hz 1 MINUTE.
 - DURABILITY: 5000 CYCLES .
 - OPERATING TEMPERATURE: -30°C TO +70°C.
 - TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
 - HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING:
 - PACKAGE: SEE "2RJ3061-008211F" PACKAGE.
 - FOR REFLOW SOLDERING LEAD-FREE PROCESS.
 - MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.
 - OTHER GENERAL SPEC. TO REFER "2RJ3061 SERIES SPEC".



PART NO.
2RJ3061-008211F

- SUFFIX: HALOGEN FREE
- PACKAGE
- 1: TAPE & REEL
- HOUSING COLOR
- 1: BLACK
- CONTACT AREA PLATING
- 2: GOLD FLASH PLATING ON CONTACT AREA, 50u" MIN. MATTE TIN PLATING ON SOLDER AREA. 30u" MIN.NICKEL UNDERPLATED OVERALL.

D	STATOR	1	SUS 301	
C	SHIELD	1	SUS 201,T=0.20	50u" MIN.NICKEL
B	CONTACT	8	C5210	SEE PART NO.
A	HOUSING	1	PA-9T UL 94V-0	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR

UNLESS OTHERWISE SPECIFIED TOLERANCES		信音科技(香港)有限公司	
DECIMALS:	ANGLES:	TITLE	RJ45 JACK, R/A, SINKING, DIP TYPE ,H=5.90mm
X :±0.5	X :±2°	DWN	EVEN 2022.01.12 PART NO. 2RJ3061-008211F
X.X :±0.3	X.X :±1°	CHKD	SCALE 3/1 UNIT: mm
X.XX :±0.2		APVD	ANGELA 2022.01.12 SIZE: A3 SHEET: 1 OF 1 REV:E
CUSTOMER COPY			