


REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PDR NO.: S121207-2A	Soldier	2013.04.10
B	ECN NO.: S130460	Soldier	2013.04.22
C	ECN NO.:S141109	Anne	2014.12.17
D	ECN NO.:S150522	Jttlucky	2015.07.31



SPECIFICATIONS:

- ELECTRICAL CHARACTERISTICS:
  - CURRENT RATING: 1.5A MAX.
  - VOLTAGE RATING: 150VAC MAX.
  - CONTACT RESISTANCE : 50mΩ MAX.(INITIAL).  
100mΩ MAX.(AFTER LIFE TEST).
  - INSULATION RESISTANCE : 100MΩ MIN.
- MECHANICAL CHARACTERISTICS:
  - DURABILITY: 5000 CYCLES.
  - INSERTION FORCE: 2.25Kg MAX. WITH LATCH DEPRESSED.
  - WITHDRAWAL FORCE: 4.5Kg MAX. WITH LATCH DEPRESSED.
  - OPERATING TEMPERATURE: -40℃ ~ +85℃
- MARKING: MARK "S" INSIDE OF THE CONNECTOR.
- PACKAGING : TAPE & REEL.
- TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
- HALOGEN FREE PRODUCT IDENTIFICATION  
MARK ON PRODUCT: ○
- HALOGEN FREE PRODUCT IDENTIFICATION LOGO  
ON THE PACKAGING: ⊗
- FOR REFLOW SOLDERING LEAD-FREE PROCESS.
- PRINTED DATE CODE" YY MM DD " ON TOP OF THE CONNECTOR.

DD: DAY  
MM: MONTH  
YY: YEAR

C	SHIELDING	1	STAINLESS STEEL	NI PLATING ALL OVER
B	8P8C CONTACT	8	PHOSPHOR BRONZE	G/F Au ON CONTACT AREA; Matte Sn 120u" ON SOLDER TAIL; ALL OVER Ni 50u"MIN.
A	BODY	1	HIGH TEMP.THERMOPLASTIC	UL 94V-0 & BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES			Singatron Enterprise Co., Ltd. 信音企業股份有限公司	
DECIMALS:		ANGLES:	TITLE	
X	:±0.5	X	±2°	DWN Jttlucky PART NO.2RJ3069-008211F
X.X	:±0.3	X.X	±1°	CHKD James SCALE 4:1 UNIT: mm
X.XX	:±0.2			APVD Boye SIZE: A3 SHEET:1 / 1 REV:D
CUSTOMER COPY				

