


REV.	ECN NO. OR DESCRIPTION	REVISED	DATE
A	PRELIMINARY	SKY	10/28/06
B	ADD DATE CODE	HAIHUA	8/07/07

SPECIFICATIONS:

- ELECTRICAL REQUIREMENTS:
 - CURRENT CARRYING RATING: 24V DC 1AMP MAX.
 - INSULATION RESISTANCE: 50 MEGOHMS MIN. AT 500V DC.
 - DIELECTRIC WITHSTANDING VOLTAGE: 250V AC FOR 1 MINUTE.
- MECHANICAL REQUIREMENTS:
 - INSERTION FORCE: 0.3KG - 1.6KG
 - WITHDRAWAL FORCE: 0.3KG - 1.4KG
 - MECHANICAL LIFE CYCLES: AFTER 5,000 CYCLES WITHOUT BREAKDOWN.
- SOLDER HEAT RESISTANCE: WAVE SOLDERING 260°C 10 SECS.
- TO CONFORM TO THE "SE-01-001" & "ROHS DIRECTIVE"
- GREEN PRODUCT IDENTIFICATION MARK IN JACK:
- GREEN PRODUCT IDENTIFICATION LABEL IN PACKING:
- FOR WAVE SOLDERING LEAD-FREE PROCESS.
- PRINTED DATE CODE "YYMMDD" ON TOP OF CONNECTOR.



NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
4	RING SPRING	1	PHOSPHOR BRASS 0.2t	SILVER PLATING
3	TIP SPRING	1	PHOSPHOR BRASS 0.3t	SILVER PLATING
2	EARTH TERMINAL	1	PHOSPHOR BRASS 0.4t	SILVER PLATING
1	BODY	1	HIGH TEMP.THERMOPLASTIC	LIME COLOR(S77C)

UNLESS OTHERWISE SPECIFIED TOLERANCES

Singatron Enterprise Co., Ltd.
信亨電子(中山)有限公司

DECIMALS:	ANGLES:	TITLE
X :±0.5	X :±2°	3.5φ PHONE JACK
X.X :±0.3	X.X :±1°	PART NO: 2SJ-0380-A02
X.XX :±0.2		SCALE: N/A UNIT: mm
		SIZE: A4 SHEET: 10F1 REV: B

CUSTOMER COPY