


REV.	ECN NO.	OR DESCRIPTION	REVISED	DATE
A		REV. NO.: 3202210-007 產品標準 料號: 申29J-051 X-XXV-25J-0510-417	Ziwei-Wu	2023.01.06

- SPECIFICATIONS:**
- ELECTRICAL CHARACTERISTICS:**
 - CONTACT RESISTANCE: $30m\Omega_{MAX}$ (INITIAL)
 - DIELECTRIC WITHSTANDING VOLTAGE: 250V AC FOR ONE MINUTE.
 - INSULATION RESISTANCE: $50M\Omega_{MIN}$. MEASURED BY 250 VDC
 - MECHANICAL CHARACTERISTICS:**
 - INSERTION FORCE : 0.2~2.5 KGF
 - WITHDRAWAL FORCE : 0.2~2.5 KGF
 - LIFE TEST: 5,000 CYCLES MIN.
 - TO CONFORM TO THE SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
 - GREEN PRODUCT IDENTIFICATION MARK ON JACK:
 - GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING:
 - FOR WAVE SOLDERING LEAD-FREE PROCESS.
 - PRINTED DATE CODE " " ON TOP OF CONNECTOR.

DATE CODE:
 DD: DAY
 MM: MONTH
 YY: YEAR



NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
A	BODY	1	COPPER ALLOY 0.5t	SILVER PLATING
B	EARTH TERMINAL	1	COPPER ALLOY 0.5t	SILVER PLATING
C	TIP SPRING	1	COPPER ALLOY 0.3t	SILVER PLATING
D	RING SPRING	1	COPPER ALLOY 0.25t	SILVER PLATING
E	SHUNT TERMINA-A	1	COPPER ALLOY 0.4t	SILVER PLATING
F	SHUNT TERMINA-B	1	COPPER ALLOY 0.4t	SILVER PLATING
G	COVER	1	THERPLASTIC	BLACK COLOR
H	GROUNDING SPRING	1	STAINLESS STEEL 0.2t	

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS:	ANGLES:
X :±0.5	X :±2°
X.X :±0.3	X.X :±1°
X.XX :±0.2	

SINGATRON Singatron Enterprise Co., Ltd.
信晉企業股份有限公司

TITLE: 3.50 PHONE JACK

DWN Ziwei-Wu | PART NO.: 25J-0510-A17

CHKD Qicai-Hu | SCALE 2:1 | UNIT: mm

APVD Jim-deng | SIZE: A3 | SHEET: 10F1 | REV: A

CUSTOMER COPY