


REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PDR:T100805-5A	Spring	2010.12.16
B	ECN: S101232	Spring	2010.12.27
C	ECN NO: S110109	Cerry	2011.03.29

SPECIFICATIONS:

- ELECTRICAL CHARACTERISTICS:**
 - 1-1. RATING: 12V 1A
 - 1-2. CONTACT RESISTANCE: 30mΩ MAX.(INITIAL)
 - 1-3. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE.
 - 1-4. INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC
- MECHANICAL CHARACTERISTICS:**
 - 2-1. INSERTION FORCE : 0.4~3.0 KGF.
 - 2-2. WITHDRAWAL FORCE : 0.3~2.0KGF.
- LIFE TEST:** 5,000 CYCLES MIN.
- OTHER GENERAL SPEC. TO REFER "2SJ-□351 SPEC".**
- PACKAGING :** TAPE & REEL.
- TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC**
- GREEN PRODUCT IDENTIFICATION MARK ON JACK:**
- GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING:** **G.P. PASS**
- FOR LEAD-FREE PROCESS.**
- DATE CODE:** YYMMDD



NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
H	SHIELDING	1	COPPER ALLOY , 0.2t	Ni 60u" Min
G	TRANSFER TERMINAL	1	PHOSPHOR BRONZE 0.2t	GOLD FLASH ON CONTACT AREA
F	BREAK TERMINAL	1	PHOSPHOR BRONZE 0.2t	Sn 120u" ON SOLDER
E	RING SPRING	1	PHOSPHOR BRONZE 0.2t	ALL OVER Ni 50u".
D	SHUNT TERMINAL-A	1	BRASS 0.25t	GOLD FLASH ON CONTACT AREA
C	TIP SPRING	1	PHOSPHOR BRONZE 0.25t	OVER Ni 50u".
B	EARTH	1	PHOSPHOR BRONZE 0.2t	Ag 20u" MIN OVER Ni 40~80u".
A	BODY +METAL	1	HIGH TEMP.THERMOPLASTIC,UL 94V-0	BLACK
			BRASS	Ni 60u" MIN

UNLESS OTHERWISE SPECIFIED TOLERANCES		Singatron Enterprise Co., Ltd. 信音企業股份有限公司		
DECIMALS:	ANGLES:	TITLE	3.5ø PHONE JACK	
X :±0.5	X :±2°	DWN	Cerry	PART NO. 2SJ-B351-S39
X.X :±0.3	X.X :±1°	CHKD	Lussen	SCALE:4:1 UNIT: MM
X.XX :±0.2		APVD	Tony	SIZE: A3 SHEET:1 OF 1 REV: C
CUSTOMER COPY				