


REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASE	AIYU	08/03'05
B	新增LIME:577C規格	HAIHUA	01/16'07
C	ECN NO:C100423 Modify Drawing	LONGJIANG	2010.10.26

- NOTES:
- 1.SPECIFICATION SEE 2.5&3.5ø PHONE JACK PRODUCT SPECIFICATION
 - 2.TO CONFORM TO THE "SE-01-001" & "ROHS DIRECTIVE"
 - 3.GREEN PRODUCT IDENTIFICATION MARK IN JACK:
 - 4.GREEN PRODUCT IDENTIFICATION LABEL IN PACKING: **G.P. PASS**
 5. FOR LEAD-FREE PROCESS.
 6. SOLDER HEAT RESISTANCE: WAVE SOLDER CONDITION 260°C 10 SECS.



CIRCUIT:

G	GROUNDING SPRING	1	STAINLESS STEEL 0.2t	
F	SHUNT TERMINA-B	1	BRASS 0.4t	SILVER PLATING
E	SHUNT TERMINA-A	1	BRASS 0.4t	SILVER PLATING
D	RING SPRING	1	COPPER ALLOY 0.25t	SILVER PLATING
C	TIP SPRING	1	COPPER ALLOY 0.3t	SILVER PLATING
B	EARTH TERMINAL	1	BRASS 0.5t	SILVER PLATING
A	BODY	1	PBT UL 94V-0	SEE TABLE
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES		Singatron Enterprise Co., Ltd. 信音企業股份有限公司		
DECIMALS: ANGLES:		TITLE 3.5ø PHONE JACK		
X	:±0.5	X	:±2°	DWN LONGJIANG 10.11.01 PART NO: 2SJ-P510-00X
X.X	:±0.3	X.X	:±1°	CHKD ZIZ 10.11.01 SCALE 5:1 UNIT: mm
X.XX	:±0.2	APVD Liao 10.11.01	SIZE: A3	SHEET: 10F1 REV: C
CUSTOMER COPY				

TABLE :

P/N	COLOR
2SJ-P510-004	LIME COLOR(577C)
2SJ-P510-002	BLUE COLOR(284C)