



REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PRODUCE RELEASE	JIANGUO	2010.11.18
B	ECN:C110131Modify Layout Dim	LONGJIANG	2011.5.30
C	ECN NO:C110149-14 Modify Plating specification	BILLY	2011.06.13

SPECIFICATIONS:

- ELECTRICAL CHARACTERISTICS:
 - 1-1. RATING:12V AC, 1A DC.
 - 1-2. CONTACT RESISTANCE: 50mΩ MAX.
 - 1-3. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE.
 - 1-4. INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC
- MECHANICAL CHARACTERISTICS:
 - 2-1. INSERTION FORCE : 0.4~3.0 KGF
 - 2-2. WITHDRAWAL FORCE : 0.3~2.0 KGF
- LIFE TEST: 5,000 CYCLES MIN.
- OTHER GENERAL SPEC. TO REFER "2SJ2285 SERIES SPEC".
- TO CONFORM TO THE SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
- HALOGEN FREE PRODUCT IDENTIFICATION MARK ON JACK:
- HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING:
- FOR REFLOW SOLDERING LEAD-FREE PROCESS.
- PACKAGING:TAPE&REEL

H	MYLAR	1	0.075T	BLACK
G	SHIELD	1	COPPER ALLOY 0.20T	Δ Au 5u" on contact area, all over Nickel plated
F	MAKE TERMINAL	1	COPPER ALLOY 0.20T	GOLD FLASH
E	TRANSFER TERMINAL	1	COPPER ALLOY 0.20T	
D	RING	1	COPPER ALLOY 0.20T	Δ Au 5u" on contact area and Gold flash on solder tail, all over Nickel Plated
C	TIP	1	COPPER ALLOY 0.25T	
B	EARTH	1	COPPER ALLOY 0.20T	GOLD FLASH
A	BODY	1	HIGH TEMP.THERMOPLASTIC UL 94V-0	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR

UNLESS OTHERWISE SPECIFIED TOLERANCES		Singatron Enterprise Co., Ltd. 信音企業股份有限公司		
DECIMALS:	ANGLES:	TITLE	3.5Ø PHONE JACK	
X :±0.5	X :±2°	DWN	BILLY 2011.6.16	PART NO. 2SJ2326-000111
X.X :±0.3	X.X :±1°	CHKD	ZJR 2011.6.15	SCALE 3:1 UNIT: mm
X.XX :±0.2		APVD	Liao 2011.6.15	SIZE: A3 SHEET: 10F1 REV: C
CUSTOMER COPY				