


RECOMMENDED P.C.B. LAYOUT T=1.00
TOP VIEW (TOLERANCE: ±0.05)



3.50 4 POLE PLUG
TOLERANCE: ±0.05

REV.	ECN NO.	OR DESCRIPTION	REVISED	DATE
C	EN NO.C10356	ADD PIN DIM	BILLY	2011.11.04
D	EN NO.C140074	MODIFY LAYOUT	ZLS	2014.7.26
E	EN NO.C140289	MODIFY TOLERANCE	ZLS	2014.12.12

SPECIFICATIONS:

1. ELECTRICAL CHARACTERISTICS:

- 1-1. RATING: 12V 1A
- 1-2. CONTACT RESISTANCE: 50mΩ MAX.
- 1-3. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE.
- 1-4. INSULATION RESISTANCE: 100 MEGOHMS BY 500V DC.

2. MECHANICAL CHARACTERISTICS:

- 2-1. INSERTION FORCE: 0.4~3.0 KGF
- 2-2. WITHDRAWAL FORCE: 0.3~2.0 KGF

3. LIFE TEST: 5 000 CYCLES MIN.

4. OTHER GENERAL SPEC. TO REFER "2SJ2285 SERIES SPEC."

5. TO CONFORM TO THE SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.


6. HALOGEN FREE PRODUCT IDENTIFICATION MARK ON JACK:

7. HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING:

8. FOR REFLOW SOLDERING LEAD-FREE PROCESS.

9. PACKAGING: TAPE & REEL.

10. DATE CODE: YMMDD



H	MYLAR	1	MYLAR 0.075T	YELLOW
G	SHIELD	1	COPPER ALLOY 0.20T	Gold flash on contact area all over Nickel Plated
F	TRANSFER TERMINAL	1	COPPER ALLOY 0.20T	Gold flash on contact area and Solder tail all over Nickel Plated
E	MAKE TERMINAL	1	COPPER ALLOY 0.20T	GOLD FLASH
D	RING	1	COPPER ALLOY 0.20T	Gold flash on contact area and Solder tail all over Nickel Plated
C	TIP	1	COPPER ALLOY 0.25T	GOLD FLASH
B	EARTH	1	COPPER ALLOY 0.20T	GOLD FLASH
A	BODY	1	HIGH TEMP THERMOPLASTIC UL 94V-0	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
Singatron Enterprise Co., Ltd. 信音企業股份有限公司				
TITLE		3.50 PHONE JACK		
DWM	14/12/23	PART NO.	2SJ2326-005111F	
CHKD	14/12/23	SCALE	3:1	
APVD	14/12/23	SIZE:	A3	SHEET: 10/1
CUSTOMER COPY				
DECIMALS:		ANGLES:		
X	: ±0.5	X	: ±2°	
X.X	: ±0.3	X.X	: ±1°	
X.XX	: ±0.2			