


RECOMMENDED P.C.B. LAYOUT T=1.00  
TOP VIEW (TOLERANCE: ±0.05)



3.5Ø 4 POLE PLUG  
TOLERANCE: ±0.05

- SPECIFICATIONS:
- ELECTRICAL CHARACTERISTICS:
    - RATING: 12V AC, 1A DC.
    - CONTACT RESISTANCE: 50mΩ MAX.
    - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE.
    - INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC.
  - MECHANICAL CHARACTERISTICS:
    - INSERTION FORCE : 0.4~3.0 KGf
    - WITHDRAWAL FORCE : 0.3~2.0 KGf
  - LIFE TEST: 5,000 CYCLES MIN.
  - OTHER GENERAL SPEC. TO REFER "2SJ2285 SERIES SPEC".
  - TO CONFORM TO THE SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
  - HALOGEN FREE PRODUCT IDENTIFICATION MARK ON JACK: ○
  - HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING: ○
  - FOR REFLOW SOLDERING LEAD-FREE PROCESS.
  - PACKAGING: TAPE&REEL.



REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASE	BILLY	2011.10.26
B	ECN NO.: C1300133 以實物修正圖面	ZLS	2013.01.25
C	ECN NO.: C140032 更新 DATE CODE	ZLS	2014.7.14

NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
H	MYLAR	1	MYLAR 0.075T	
G	SHIELD	1	COPPER ALLOY 0.20T	Gold flash on contact area all over Nickel Plated
F	TRANSFER TERMINAL	1	COPPER ALLOY 0.20T	Gold flash on contact area and Silver flash over Nickel Plated
E	MAKE TERMINAL	1	COPPER ALLOY 0.20T	GOLD FLASH
D	RING	1	COPPER ALLOY 0.20T	Gold flash on contact area and Solder flash over Nickel Plated
C	TIP	1	COPPER ALLOY 0.25T	
B	EARTH	1	COPPER ALLOY 0.20T	GOLD FLASH
A	BODY	1	HIGH TEMP THERMOPLASTIC UL 94V-0	BLACK

Singatron Enterprise Co., Ltd.  
信登企業股份有限公司

TITLE	3.5Ø PHONE JACK
DWN	ZS 14/7/21 PART NO. 2SJ2326-011111F
CHKD	BILLY 14/7/21 SCALE 3:1 UNIT: mm
APVD	Luo 14/7/21 SIZE: A3 SHEET: 10F1 REV: C