


RECOMMENDED P.C.B. LAYOUT T=1.0  
TOP VIEW (TOLERANCE: ±0.05)



3.5Ø 4 POLE PLUG  
TOLERANCE: ±0.05

SPECIFICATIONS:

- ELECTRICAL CHARACTERISTICS:
  - RATING: 12V, 1A.
  - CONTACT RESISTANCE: 50mΩ MAX.
  - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE.
  - INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC.
- MECHANICAL CHARACTERISTICS:
  - INSERTION FORCE: 0.4~3.0 KGF
  - WITHDRAWAL FORCE: 0.3~2.0 KGF
  - LIFE TEST: 5,000 CYCLES MIN.
  - OTHER GENERAL SPEC. TO REFER "2SJ2285 SERIES SPEC."
  - TO CONFORM TO THE SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
  - HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON JACK: ©
  - HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING: ©
  - FOR REFLOW SOLDERING LEAD-FREE PROCESS.
  - PACKAGING: TAPE&REEL.



REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASE	ZJS	2013.01.09
B	ECN NO.: C130037 增加绝缘材料, 增加绝缘材料	ZJS	2013.04.29

NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
H	MYLAR	1	0.075T	BLACK
G	SHIELD	1	COPPER ALLOY 0.20T	Au 5u" on contact area All over Ni-plated
F	TRANSFER TERMINAL	1	COPPER ALLOY 0.20T	Gold flash on contact area and Solder tail, all over Nickel Plated
E	MAKE TERMINAL	1	COPPER ALLOY 0.20T	Au 5u" on contact area and gold flash on Solder tail all over Nickel Plated
D	RING	1	COPPER ALLOY 0.20T	
C	TIP	1	COPPER ALLOY 0.25T	Au 5u" on contact area And G/F other area
B	EARTH	1	COPPER ALLOY 0.20T	
A	BODY	1	HIGH TEMP.THERMOPLASTIC UL 94V-0	BLACK

UNLESS OTHERWISE SPECIFIED TOLERANCES	ANGLES:
DECIMALS:	X : ±0.5 X : ±2°
	X.X : ±0.3 X.X : ±1°
	X.XX : ±0.2

TITLE	3.5Ø PHONE JACK
DWN	ZJS 13/5/2 PART NO. 2SJ2326-026111F
CHKD	ZJS 13/5/2 SCALE 3:1 UNIT: mm
APVD	Luo 13/5/2 SIZE: A3 SHEET: 10F1 REV: B

CUSTOMER COPY

UNLESS OTHERWISE SPECIFIED TOLERANCES

Singatron Enterprise Co., Ltd.  
信音企業股份有限公司