



RECOMMENDED P.C.B. LAYOUT
TOP VIEW (TOLERANCE: ±0.05)



- NOTE:
- ELECTRICAL CHARACTERISTICS:
 - CURRENT RATING: 1AMPERE PER CONTACT.
 - CONTACT RESISTANCE: 50mΩ MAX.(INITIAL), 100Ω MAX(AFTER LIFE TEST)
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE.
 - INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC.
 - MECHANICAL CHARACTERISTICS:
 - INSERTION AND WITHDRAWAL FORCE : 0.4~3.0 KGf(INITIAL)
 - INSERTION AND WITHDRAWAL FORCE : 0.3~3.0 KGf(AFTER LIFE TEST)
 - LIFE TEST: 15,000 CYCLES.
 - OTHER GENERAL SPEC. TO REFER "2SJ2364-00X111F SPEC."
 - TO CONFORM TO THE SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
 - HALOGEN FREE PRODUCT IDENTIFICATION MARK ON JACK: ◎
 - HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING: ◎
 - FOR REFLOW SOLDERING LEAD-FREE PROCESS.
 - PACKAGING:TAPE&REEL.
 - PART NO DEFINE:



P/N	BODY COLOR
2SJ2364-002111F	PINK
2SJ2364-003111F	LIME

F	RING	1	COPPER ALLOY 0.2T	Gold Flash over Ni plated
E	MAKE TERMINAL	1	COPPER ALLOY 0.2T	Gold Flash over Ni plated
D	TRANSFER	1	COPPER ALLOY 0.2T	Gold Flash over Ni plated
C	TIP	1	COPPER ALLOY 0.25T	Gold Flash over Ni plated
B	EARTH	1	COPPER ALLOY 0.3T	Gold Flash over Ni plated
A	BODY	1	HIGH TEMP. THEROPLASTIC UL 94V-0	SEE NOTE 10.
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR

UNLESS OTHERWISE SPECIFIED TOLERANCES

Singatron Enterprise Co., Ltd.
信音企業股份有限公司

DECIMALS:	ANGLES:	TITLE	3.5mm PHONE JACK
X : ±0.5	X : ±2°	DWN	ZLS 14/5/16
X.X : ±0.3	X.X : ±1°	CHKD	ZLZ 14/5/16
X.XX : ±0.2		APVD	lsoo 14/5/16
CUSTOMER COPY			