



- SPECIFICATIONS:**
- ELECTRICAL CHARACTERISTICS:**
    - 1-1. RATING: 12V 1A
    - 1-2. CONTACT RESISTANCE: 50mΩ MAX (INITIAL)
    - 1-3. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE
    - 1-4. INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC
  - MECHANICAL CHARACTERISTICS:**
    - 2-1. INSERTION FORCE: 0.8~3.0kgf INITIAL ; 2.5 kgf Max. After THE 2000th
    - 2-2. WITHDRAWAL FORCE: 0.6~1.8kgf INITIAL; 0.5 kgf Min. After THE 2000th
  - LIFE TEST: 2,000 CYCLES MIN.
  - AFTER LIFE TEST, CONTACT RESISTANCE: 100mΩ MAX.
  - PACKAGING : TAPE & REEL.
  - MARKING: MARK "S" ON CONNECTOR.
  - TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
  - HALOGEN FREE PRODUCT IDENTIFICATION MARK ON PRODUCT:
  - HALOGEN FREE PRODUCT IDENTIFICATION LOGO ON PACKAGING:

2SJS3080-129X11F

1:G/F  
2:Au 30u"

I	SHELL	1	SUS304 1/2H, 0.2t	Ni 60u Min.
H	SEPARATOR	1	HIGH TEMP.THERMOPLASTIC UL 94V-0	BLACK
G	MAKE TERMINAL	1	PHOSPHOR BRONZE 0.2t	GOLD FLASH ON CONTACT AREA; GOLD FLASH ON SOLDER AREA; ALL OVER 50u" Ni.
F	EARTH	1	PHOSPHOR BRONZE 0.2t	SEE TABLE ON CONTACT AREA; GOLD FLASH ON SOLDER AREA; ALL OVER 50u" Ni.
E	TRANSFER TERMINAL	1	PHOSPHOR BRONZE 0.2t	GOLD GLASH ON CONTACT AREA; Matte Sn120u" ON SOLDER AREA; ALL OVER 50u" Ni.
D	TIP SPRING	1	SUS304 1/2H 0.2t	SEE TABLE ON CONTACT AREA; GOLD FLASH ON SOLDER AREA; ALL OVER 50u" Ni.
C	RING A	1	PHOSPHOR BRONZE 0.2t	SEE TABLE ON CONTACT AREA; Matte Sn120u" ON SOLDER AREA; ALL OVER 50u" Ni.
B	RING B	1	PHOSPHOR BRONZE 0.2t	SEE TABLE ON CONTACT AREA; Matte Sn120u" ON SOLDER AREA; ALL OVER 50u" Ni.
A	BODY	1	HIGH TEMP.THERMOPLASTIC UL 94V-0	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
Singatron Enterprise Co., Ltd. 信晉企業股份有限公司				
<b>TITLE</b> 3.5Φ AUDIO JACK <b>DWN</b> Qing <b>PART NO.</b> 2SJS3080-129X11F <b>CHKD</b> Bruce <b>SCALE</b> 2:1 <b>UNIT:</b> mm <b>APVD</b> Loo <b>SIZE:</b> A3 <b>SHEET:</b> 1 OF 1 <b>REV:</b> A				
<b>CUSTOMER COPY</b>				