



TOLERANCE :±0.3mm UNLESS OTHERWISE SPECIFIED

9.	Washer	0.4T Brass	1	Nickel Plated
8.	Nut	2.2T Brass	1	Nickel Plated
7.	Housing	PBT	1	Black Color
6.	Barrel	Brass	1	Nickel Plated
5.	Ring Shunt	0.4T Brass	1	Silver Plated
4.	Ring Spring	0.4T Phosphor Bronze	1	Silver Plated
3.	Tip Spring	0.4T Phosphor Bronze	1	Silver Plated
2.	Tip Shunt	0.4T Brass	1	Silver Plated
1.	Earth Terminal	0.4T Brass	1	Silver Plated
NO.	Description	Material	Q 'TY	Finish

RoHS
Compliant

For Reference
僅供參考

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: ▲ : The Most Important Dimension

Singatron Enterprise Co., Ltd.

TITLE	6.3φ PHONE JACK		
DWN	10.12.2011	PART NO.	2SJ649-M1NUS4B00G
CHKD	SCALE 1:1	UNIT:	mm
APVD	SIZE: A3	SHEET: 1 OF 1	REV: 2.0
CUSTOMER COPY			