



RECOMMENDED P.C.B. LAYOUT T=1.60  
TOP VIEW (TOLERANCE: ±0.05)

REV. ECN NO OR DESCRIPTION	REVISED	DATE
A INITIAL RELEASE	ZHIWEI G	2011.07.07

- SPECIFICATION**
- ELECTRICAL CHARACTERISTICS:
    - VOLTAGE & CURRENT RATING: DC 30V MAX & 1.5A
    - CONTACT RESISTANCE: 30mΩ MAX.
    - INSULATION RESISTANCE: 1000MΩ MIN.
    - DIELECTRIC WITHSTAND: 500V AC for 1 MINUTE
    - OPERATING TEMPERATURE: -55°C ~ +85°C
  - MECHANICAL CHARACTERISTICS:
    - INSERT FORCE: 35N MAX.
    - WITHDRAW FORCE: 10N MIN.
  - LIFE TEST: 1500 CYCLES
  - OTHER GENERAL SPEC. TO REFER "2UB2Y13 SERIES SPEC"
  - PACKING: SOFT TRAY
  - HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING:
  - PART NO:

2UB2Y13-0 X X X 1 1 1

HOUSING MATERIAL: \_\_\_\_\_  
0=LOW TEMP THERMOPLASTIC

CONTACT AREA PLATED: \_\_\_\_\_  
00=1~30" Au  
30=30u" Au

PACKAGE TYPE: \_\_\_\_\_  
1=SOFT TRAY

REAR SHELL TYPE: \_\_\_\_\_  
1=W/ REAR SHELL

DURABILITY: \_\_\_\_\_  
1=1500 CYCLES

C	CONTACT	4	COPPER ALLOY 0.2T	Au 1~3u"Min; Ni PLATING OVERALL
B	SHELL	1	BRASS 0.3T	Ni PLATING
A	HOUSING	1	LOW TEMP PLASTIC UL94V-0	WHITE
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
Singaton Enterprise Co., Ltd. 信登企業股份有限公司				
TITLE		USB A/F DIP 90° TYPE		
DWN	ZHIWEI G	PART NO.	2UB2Y13-0XX111	
CHKD	TONY	SCALE	4:1	UNIT: mm
APVD	SEAN-L	SIZE:	A3	SHEET: 10F1
REV. A				
CUSTOMER COPY				

2UB2Y13-000111
2UB2Y13-030111

