



SPECIFICATIONS:

- ELECTRICAL CHARACTERISTICS:
  - RATING: P1&P5 AC 30V 1.8A/0.5A FOR PIN2&PIN3&PIN4
  - CONTACT RESISTANCE: 50m MAX.(INITIAL)
  - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE.
  - INSULATION RESISTANCE: 100M MIN. MEASURED BY 500 VDC
- MECHANICAL CHARACTERISTICS:
  - INSERTION FORCE: 2.5KGF MAX.
  - WITHDRAWAL FORCE: 1.0KGF - 2.0KGF.
  - LIFE TEST: 5000 CYCLES MIN.

NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
C	SHELL	1	STAINLESS STEEL,0.3T	ALL OVER N° 60 u" Min
B	TERMINAL	1	Phosphor bronze	GOLD FLASH ON CONTACT AREA GOLD FLASH ON SOLDER PAL ALL OTHER N° 30 u" Min
A	BODY	1	LCP UL 94V-0	BLACK

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS:	ANGLES:
X :±0.5	X :±2°
XX :±0.3	XX :±1°
XXX :±0.2	

TITLE	MICRO USB REVERSE
DWN	Edi.Zhou
CHKD	Boye
APVD	Boye

PART NO.	SCALE	UNIT	SHEET	REV.
2UB3800-003011F	A/A	mm	1 OF 1	A

CUSTOMER COPY

REV	ECN NO	OR DESCRIPTION	REVISED	DATE
A	PDR NO. T150116-6A		Edi.Zhou	2015.04.28