



SPECIFICATION

1. CONTACT CURRENT RATING 1.0A AT 250V AC
2. CONTACT RESISTANCE 30mΩ max.
3. INSULATION RESISTANCE 100MΩ min
4. DIELECTRIC WITHSTANDING VOLTAGE 100V AC FOR 1 MINUTE
5. INSERTION FORCE 3.5Kg Max
6. EXTRACTION FORCE 0.7Kg MIN(INITIAL) 0.3Kg MIN(5000 CYCLE)
7. DURABILITY 5000 INSERTION/EXTRACTION CYCLE
8. OPERATING TEMPERATURE -55~85°
9. PACKAGING: TAPE & REEL
10. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
11. GREEN PRODUCT IDENTIFICATION MARK ON JACK:
12. GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING:
13. FOR WAVE SOLDERING LEAD-FREE PROCESS.

ORDER INFORMATION:

2 U B 4 0 0 0 - 0 0 0 1 1 1

PACKAGING: T&R  
 BODY COLOR: BLACK; PA-9T  
 CONTACT PLATING 30u"Au

D	MYLAR	1	KAPTON	YELLOW
C	SHELL	1	COPPER ALLOY 0.4T	PLATED 60u" Ni
B	TERMINAL	5	COPPER ALLOY 0.2T	CONTACT 30u"Au SOLDER TAIL 120u"Sn
A	BODY	1	THERMOPLASTIC UL 94V-0	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR

Singatron Enterprise Co., Ltd.  
 信登企業股份有限公司

UNLESS OTHERWISE SPECIFIED TOLERANCES	DECIMALS:	ANGLES:	TITLE	MINI USB I=7.5mm AB TYPE/SMT CONNECTOR
	X : ±0.50	X : ±2°	DWN	Victor 2008.7.31
	X.X : ±0.30	X.X : ±1°	CHKD	Mark 2008.7.31
	X.XX : ±0.20		APVD	Mark 2008.7.31
			SCALE:	1/1
			UNIT:	mm
			SHEET:	1 OF 1
			REV:	B

CUSTOMER COPY

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASED	Brian	07/06/07
B	ECN_W080010	Victor	07/30/08