



SPECIFICATION

1. CONTACT CURRENT RATING 1.0A AT 250V AC
2. CONTACT RESISTANCE 30mΩ max.
3. INSULATION RESISTANCE 100M Ωmin
4. DIELECTRIC WITHSTANDING VOLTAGE 100V AC FOR 1 MINUTE
5. INSERTION FORCE 3.5kg Max
6. EXTRACTION FORCE 0.7kg MIN(INITIAL) 0.3kg MIN(5000 CYCLE)
7. DURABILITY 5000 INSERTION/EXTRACTION CYCLE
8. OPERATING TEMPERATURE -55~85°
9. PACKAGING: TAPE & REEL
10. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
11. GREEN PRODUCT IDENTIFICATION MARK ON JACK:
12. GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING:
13. FOR WAVE SOLDERING LEAD-FREE PROCESS.

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	Product Release	Victor	12/15/08
B	ECN NO: W090022	Victor	8/13/09

NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
D	MYLAR	1	KAPTON	YELLOW
C	SHELL	1	COPPER ALLOY 0.4T	PLATED 30u" Ni OVER 50u" Sn
B	TERMINAL	5	COPPER ALLOY 0.2T	CONTACT 30u" Au SOLDER TAIL 120u" Sn
A	BODY	1	THERMOPLASTIC UL 94V-0	BLACK

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS:	ANGLES:
X : ±0.50	X : ±2°
X.X : ±0.30	X.X : ±1°
X.XX : ±0.20	

TITLE	MINI USB L=7.5mm AB TYPE/SMT CONNECTOR
DWN	Victor 2008.13 PART NO. 2UB4000-001111
CHKD	Victor 2008.13 SCALE: 1/1 UNIT: mm
APVD	Victor 2008.13 SIZE: A3 SHEET: 1 OF 1 REV: B

CUSTOMER COPY

Singatron Enterprise Co., Ltd.  
信亨企業股份有限公司