



F	MYLAR	1	KAPTAN 11.0x9.5	YELLOW
E	TERMINAL	5	COOPER ALLOY	1.0" Au Plated ON CONTACT AREA, 100% WASTE SN PLATED ON SOLDERING 60u-150u/NICKEL UNDER PLATING OVERALL
D	TERMINAL	4	COOPER ALLOY	
C	SHELL	1	STAINLESS STEEL	NICKEL 60U"MIN
B	BASE	1	HIGH THERMOPLASTIC	BLUE (300C)
A	HOUSING	1	HIGH THERMOPLASTIC	BLUE (300C)
NO	DESCRIPTION		MATERIAL	PLATING & COLOR

**SPECIFICATIONS:**

- ELECTRICAL CHARACTERISTICS:
  - CURRENT RATING: 1.8A (PIN1,4) ; OTHER CONTACTS 0.25A
  - CONTACT RESISTANCE: 30mΩ MAX.
  - CONTACT WITHSTANDING VOLTAGE: 100V AC FOR 1 MINUTE
  - DIELECTRIC WITHSTANDING VOLTAGE: 100V AC FOR 1 MINUTE
  - INSULATION RESISTANCE: 100MΩ MIN
  - TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
  - TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
  - HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON JACK: ©
  - HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING: ©
  - FOR REFLOW SOLDERING LEAD-FREE PROCESS.
- DATE : YMMDD
- PACKAGING : TAPE & REEL.

REV.	ECN NO.	OR DESCRIPTION	REVISED	DATE
B	ECN NO: T120047		Even	2012.06.11
C	ECN NO: S120646		Tom	2012.06.28
D	ECN NO: S121223		Angus	2013.05.24
E	ECN NO: S151126-C		peng	2016.01.04
F	ECN NO: S170954-R		Song	2017.11.09

UNLESS OTHERWISE SPECIFIED TOLERANCES		SINGATRON ENTERPRISE CO., LTD. 信昌企業股份有限公司	
DECIMALS:	ANGLES:	TITLE	
X : ±0.5	X : ±2'	USB 3.0 REVERSE CONNECTOR	
X.X : ±0.3	X.X : ±1'	DWN	Song
X.XX : ±0.2		CHKD	James
		APVD	Boye
		PART NO. 2UB4008-300101F	
		SCALE 1:1	
		UNIT: mm	
		SHEET: 1 OF 1	
		REV: F	
CUSTOMER COPY			