



- SPECIFICATIONS:**
- ELECTRICAL CHARACTERISTICS:**
 - 1-1. CURRENT RATING: 1.8A (PIN1,4) ; OTHER CONTACTS 0.25A
 - 1-2. CONTACT RESISTANCE: 30mΩ MAX.
 - 1-3. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE
 - 1-4. INSULATION RESISTANCE: 100MΩ MIN
 - MECHANICAL CHARACTERISTICS:**
 - 2-1. INSERTION FORCE : 35N MAX
 - 2-2. WITHDRAWAL FORCE : 8N MIN
 - DURABILITY:** 1500 CYCLES.
 - TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.**
 - HALOGEN FREE PRODUCT IDENTIFICATION MARK IN JACK: (C)**
 - HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING: (E)**
 - FOR REFLOW SOLDERING LEAD-FREE PROCESS.**
 - PACKAGING : TAPE & REEL.**

REV.	EGN NO.	OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASE		Chunxiaol	2014.06.23

NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
C	TERMINAL	4	PHOSPHOR BRONZE	GOLD FLASH
B	SHELL	1	SUS	NICKEL PLATED
A	HOUSING	1	THERMAL PLASTIC	BLACK

UNLESS OTHERWISE SPECIFIED TOLERANCES

Singatron Enterprise Co., Ltd.
信晉企業股份有限公司

DECIMALS:	ANGLES:	TITLE
X :±0.5	X :±2°	USB2.0 CONNECTOR
X.X :±0.3	X.X :±1°	DWN
X.XX :±0.2		CHKD
		APVD

CUSTOMER COPY