


- SPECIFICATIONS:
- ELECTRICAL CHARACTERISTICS:
 - 1-1. ELECTRICAL RATING: 1.8A (PIN1,4) ; OTHER CONTACTS 0.25A
 - 1-2. CURRENT RATING: 30mA MAX
 - 1-3. CONTACT RESISTANCE: 30mΩ MAX
 - 1-4. DIELECTRIC WITHSTANDING VOLTAGE: 100V AC FOR 1 MINUTE
 - MECHANICAL CHARACTERISTICS:
 - 2-1. INSERTION FORCE : 3.5 Kgf MAX
 - 2-2. WITHDRAWAL FORCE : 1.0 kgf (INITIAL), 0.8kgf (AFTER TEST)
 3. DURABILITY: 5,000 CYCLES.
 4. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
 5. HALOGEN FREE IDENTIFICATION MARK ON JACK:
 6. HALOGEN FREE IDENTIFICATION LABEL ON PACKAGING:
 7. FOR IR-REFLOW LEAD-FREE PROCESS.
 8. DATE : YMMDD
 9. PACKAGING : TAPE & REEL.



Terminal	Material	Plating	Pin Number	Signal Assignment
E	TERMINAL	COOPER ALLOY	PIN 1	VBUS
D	TERMINAL	COOPER ALLOY	PIN 2	D-
C	SHELL	STAINLESS STEEL	PIN 3	D+
B	BASE	HIGH THERMOPLASTIC	PIN 4	GND
A	HOUSING	HIGH THERMOPLASTIC	PIN 5	SDA_SSRX-
NO	DESCRIPTION	MATERIAL	PIN 6	SDA_SSRX+
			PIN 7	GND_DRAIN
			PIN 8	SDA_SSTX-
			PIN 9	SDA_SSTX+

Terminal	Material	Plating & Color	Thickness	Notes
E	TERMINAL	COOPER ALLOY	22"μm OVER 30μ"7μ"Ni PLATED ON WATERS AREA, 120μ" Sn PLATED ON SOLDERING	
D	TERMINAL	COOPER ALLOY	80μ"Nickel UNDER PLATING OVERALL	
C	SHELL	STAINLESS STEEL	NICKEL 60μ"MIN	
B	BASE	HIGH THERMOPLASTIC	BLUE (300C)	
A	HOUSING	HIGH THERMOPLASTIC	BLUE (300C)	
NO	DESCRIPTION	MATERIAL	PLATING & COLOR	

DECIMALS:	ANGLES:
X : ±0.5	X : ±2°
X.X : ±0.3	X.X : ±1'
X.XX : ±0.2	

TITLE	Part No.
USB 3.0 REVERSE CONNECTOR	2UB34060-800101F
DWN	Duke
CHKD	SCALE 1:1
APVD	APVD
	SIZE: A3
	SHEET: 1 OF 1
	REV: A

Singatron Enterprise Co., Ltd.
信音企業股份有限公司

CUSTOMER COPY