



REV	ECN NO OR DESCRIPTION	REVISED	DATE
E	1.ECN NO.C080280-4/4 2.ADD HF LOGO	HAHUA	12/16/08
F	Modify tolerance ECN NO.C080287-3/4	HAHUA	5/21/09
G	Modify ECN NO.C1000008-1/3	Sticky-hu	2010.03.02

**SPECIFICATIONS:**

- ELECTRICAL CHARACTERISTICS:
  - RATING: 30V 1A
  - CONTACT RESISTANCE: 30mΩ MAX.(INITIAL)
  - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE.
  - INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC.
- TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
- HALOGEN FREE PRODUCT IDENTIFICATION MARK ON PRODUCT: ☉
- HALOGEN FREE PRODUCT IDENTIFICATION LOGO ON PACKAGING: ☉
- FOR REFLOW SOLDERING LEAD-FREE PROCESS.
- DATE CODE: X X X X  
 Day  
 Month  
 Year
- ORDER NO.  
2UP2002-4P1111

- PACKING
- 1.TAPE & REEL
- BODY COLOR
- 1.BLACK
- CONTACT PLATING
- Au15u"
- SINKING TYPE
- HIGH:2.4mm

C	SHELL	1	SPPC T=0.3±0.01	NI20u"/Cu80u"
B	CONTACT	1	COPPER ALLOY T=0.25±0.01	Au15u"
A	INSERT MOULDING	1	HIGH TEMP.THERMOPLASTIC, UL94V-0	BLACK COLOR
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS:	ANGLES:	Singatron Enterprise Co., Ltd. 信晉企業股份有限公司	
X : ±0.5	X : ±2°	TITLE	USB 2.0 SMT PLUG(LEG 3.8mm)
X.X : ±0.3	X.X : ±1'	DWN	Stick+ho PART NO. 2UP2002-4P1111
X.XX : ±0.2		CHKD	MIDYUAN SCALE 4:1 UNIT: mm
		APVD	ROBIN SIZE: A4 SHEET: 10F1 REV: G

CUSTOMER COPY