


4	WHITE (28AWG)
3	GREEN(28AWG)
2	BLACK(24AWG)
1	RED (24AWG)
	WIRE COLOR
	PIN OUT



- NOTES:
1. WATERPROOF RATE: IP67(WHEN PROPERLY MATED)  
IP67: IMMersed IN 1M WATER FOR 30 MINUTES
  2. RATING:30V 1A
  3. OTHER GENERAL SPEC. TO REFER "2UP2002 SERIES SPEC."
  4. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
  5. GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING:
  7. TEMPERATURE RANGE: -20~80℃
  8. TIGHTENING TORQUES: 0.8~1.0Nm(7.08~8.85lbf.in.).
  9. SCREW NUT无需组装作附件随包装出货。



NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
I	WIRE	1	28AWG VW-1	WHITE
H	WIRE	1	28AWG VW-1	GREEN
G	WIRE	1	24AWG VW-1	BLACK
F	WIRE	1	24AWG VW-1	RED
E	SCREW NUT	1	PC UL94V-0	BLACK
D	BODY	1	PPE 540Z UL94V-0	BLACK
C	GUIDE GLUE	1	JA940-4	BLACK
B	USB A PLUG	1	USB 2.0 UL94V-0	N/A
A	GASKET	1	Silicone	BLACK

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS:	ANGLES:	TITLE
X :±0.5	X :±2°	WATERPROOF USB2.0 A Plug
X.X :±0.3	X.X :±1°	
X.XX :±0.2		

DMN	JAY	PART NO.2UP3000-W05119H
CHKD	MF	SCALE 2:1 UNIT: mm
APVD	JF	SIZE: A3 SHEET:1 OF 1 REV: B

CUSTOMER COPY

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PDR NO. A200915-6A	JAY	2021.12.04
B	ECN NO.:S202211-R10	JAY	2022.11.22