



- SPECIFICATIONS**
- Voltage Rating : 250V AC/DC
 - Current Rating : 2A AC/DC
 - Withstanding Voltage : 1000V AC/minute
 - Insulation Resistance : 1000M Ω min.
 - Temperature Range : - 40 $^{\circ}$ C to + 105 $^{\circ}$ C
 - Contact Resistance : 20m Ω max.
- HOUSING**
- Part No. : 2WB1126-XX
 - Poles : 1~40 (Single Row)
 - Material : Noryl UL94V-1
 - Qty : 1,000 pcs./Bag

Poles	Dimensions(mm)		Dimensions(mm)	
	A	B	A	B
1	—	2.20	21	40.00
2	2.00	4.20	22	42.00
3	4.00	6.20	23	44.00
4	6.00	8.20	24	46.00
5	8.00	10.20	25	48.00
6	10.00	12.20	26	50.00
7	12.00	14.20	27	52.00
8	14.00	16.20	28	54.00
9	16.00	18.20	29	56.00
10	18.00	20.20	30	58.00
11	20.00	22.20	31	60.00
12	22.00	24.20	32	62.00
13	24.00	26.20	33	64.00
14	26.00	28.20	34	66.00
15	28.00	30.20	35	68.00
16	30.00	32.20	36	70.00
17	32.00	34.20	37	72.00
18	34.00	36.20	38	74.00
19	36.00	38.20	39	76.00
20	38.00	40.20	40	78.00

The first triangle mark from the left is PIN1.
Other triangle marks are for friendly counting uses.

TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
.0	△	RoHS Compliant	2006/04/01	徐秀麗	△			
.00	△	2008011-025	2008/11/28	黃科源	△			
.000	△	2008012-015	2008/12/15	黃科源	△			
	△	200903-012	2009/03/24	黃科源	△			
ANGLE	△	變更三角形位置,增加註解	2012/07/03	張育端	△			
0	△				△			
.0°	±				△			
SHEET	1/1				△			

CUSTOMER				CUSTOMER			
Conforms to The RoHS Instruction				Conforms to The RoHS Instruction			
Singatron Enterprise Co., Ltd.							
TITLE 2.00mm Center Mini Latch Housing							
DWN 張逸維		PART NO. 2WB1126-XX		APVD 張育端		SIZE: A3	
CHKD 黃科源		SCALE 1:1		SHEET: 1 OF 1		REV: d5	
CUSTOMER COPY							

