



Poles	Dimensions(mm)	
	A	B
2	2.50	5.80
3	5.00	8.30
4	7.50	10.80
5	10.00	13.30
6	12.50	15.80
7	15.00	18.30
8	17.50	20.80
9	20.00	23.30
10	22.50	25.80
11	25.00	28.30
12	27.50	30.80
13	30.00	33.30
14	32.50	35.80
15	35.00	38.30

- SPECIFICATIONS**
- Voltage Rating : 250V AC/DC
 - Current Rating : 3A AC/DC
 - Withstanding Voltage : 1,000V AC/minute
 - Insulation Resistance : 1,000M Ω min
 - Temperature Range : -25℃ to + 85℃
 - Contact Resistance : 20m Ω max

- HOUSING**
- Part No. : 2WB1136-XX
 - Code No. ①
 - Poles : 2 - 15
 - Material : Nylon 66 UL94V-2
 - Q'ty: 1,000 pcs./Bag

TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
.0	△	ECR 200810-005	黃桂源	2008/10/22	△			
.00	△	更正三角記號位置, 尺寸依實物修正	吳弘文	2013/09/23	△			
.000	△	修定05.07P B尺寸	吳弘文	2014/08/16	△			
ANGLE								
0°	△							
±1°	△							
±	△							
0°	△							
±	△							
SHEET	1/1							

CUSTOMER	REVISION RECORD	NAME	DATE
Conforms to The RoHS Instruction			

Singatron Enterprise Co., Ltd.			
2.50mm Crimp Style Connectors Housing			
DWN	吳弘文	PART NO.	2WB1136-XX
CHKD	周慈雲	SCALE	1:1
APVD	張育瑞	SIZE	A3
		SHEET	1 OF 1
		REV	03
CUSTOMER COPY			