



■ **SPECIFICATIONS**

- Current rating : 1A AC/DC
- Withstanding voltage : 500V AC/minute
- Insulation resistance : 500M Ω min.
- Temperature range : -35°C to +85°C
- Contact resistance : 30m Ω max.

■ **WAEER**

- Part No. : 2WB1246R-XX(X)

Poles ←
Plated ←
Blank:Gold
T: Tin

- Poles : 02-15
- Material :
 1. Contact : Phos. Bronze
 2. Solder Nail : Phos. Bronze
 3. Base : Nylon 6T UL94V-0
- Plated : Refer the above options
- Q' ty : 1,000pcs./ Reel

Poles	Dimensions(mm)		
	A	B	C
2	1.25	4.15	6.25
3	2.50	5.40	7.50
4	3.75	6.65	8.75
5	5.00	7.90	10.00
6	6.25	9.15	11.25
7	7.50	10.40	12.50
8	8.75	11.65	13.75
9	10.00	12.90	15.00
10	11.25	14.15	16.25
11	12.50	15.40	17.50
12	13.75	16.65	18.75
13	15.00	17.90	20.00
14	16.25	19.15	21.25
15	17.50	20.40	22.50

TOLERANCE	LTR	REVISION RECORD	NAME	DATE
.0	±0.30	▲ 新增鍍金規格	王誠賢	2011/12/14
.00	±0.20	▲		
.000	±0.10	▲		
ANGLE		▲		
0°	±1°	▲		
.0°	±	▲		
SHEET	1/1	▲		

Singatron Enterprise Co., Ltd.

TITLE 1.25mm Wire to Board Conn, 90° & SMT Type

DWN 王誠賢 PART NO. 2WB1246R-XX(X)

CHKD 黃科源 SCALE 1:1 UNIT: mm

APVD 張育瑞 SIZE: A3 SHEET: 1 OF 1 REV: a1

CUSTOMER COPY