



■ SPECIFICATIONS

- Voltage Rating : 150V AC/DC
- Current Rating : 1A AC/DC
- Withstanding Voltage : 500V AC/minute
- Insulation Resistance : 500M Ω min.
- Temperature Range : - 35 $^{\circ}$ C to + 85 $^{\circ}$ C
- Contact Resistance : 30m Ω max.

■ WAFER

- Part No. : 2WB1247-XX (DIP Type)
- Poles : 2-15(Straight)
- Material : Contact : Brass, Tin Plated
Bass : Nylon 66 UL94V-0
- Q' ty : 1,000 pcs./Box

Poles	Part No	Dimensions(mm)	
		A	B
2	2WB1247-02	1.25	3.75
3	2WB1247-03	2.50	5.00
4	2WB1247-04	3.75	6.25
5	2WB1247-05	5.00	7.50
6	2WB1247-06	6.75	8.75
7	2WB1247-07	7.50	10.00
8	2WB1247-08	8.75	11.25
9	2WB1247-09	10.00	12.50
10	2WB1247-10	11.25	13.75
11	2WB1247-11	12.50	15.00
12	2WB1247-12	13.75	16.25
13	2WB1247-13	15.00	17.50
14	2WB1247-14	16.25	18.75
15	2WB1247-15	17.50	20.00

TOLERANCE		LTR	REVISION RECORD	DATE
.0	±0.3	ECR	RoHS compliant	06/06/26
.00	±0.2	ECR	200806-032	08/06/27
.000	±0.1	ECR	200811-014	08/11/17
ALL	±			
ANGLE				
0°	±			
.0°	±			

Singatron Enterprise Co., Ltd.

TITLE	1.25mm Disconnectable crimp style connectors Wafer
DWN	黄科源
CHKD	张育瑞
APVD	林宗
PART NO.	2WB1247-XX
SCALE	1:1
UNIT	mm
SIZE	A3
SHEET	1 OF 1
REV	a2

CUSTOMER COPY